

Haier



Laboratory Refrigerator Operation Manual

Model:
HLR-198F
HLR-310F

Certificate of Quality

checker:



Manufacturer: Qingdao Haier Biomedical Co., Ltd.
Address: Haier Industrial Park, Economic Technology Development
Zone. Qingdao P.R.China
Web: www.haiermedical.com
Revision Date: 09/2018
Version: 2nd, 2018
Dedicated code: 0270501299N
V13026

- Please read this instruction carefully before using.
- Our company reserves the right to interpret the User's Manual.
- The appearance of product is subject to material object.
- Please keep it properly with the invoice after reading.
- This product is subject to technology or software upgrade without further notice.
- Translation of the original instruction.



Haier quality, it merits your trust from beginning to end.

This product is applicable to university laboratories, research units, test locations etc. for storage of test reagents.

Temperature Control

The product application scope: Temperature setting range 3°C ~ 16°C .
Computer control and temperature numeric display with temperature display precision of 1°C .

Safety System

- Multiple fault alarms (hi-low temperature alarm, sensor fault alarm, door alarm)
- Two modes for alarms (sound buzzer and alarm lamp flickering)
- All independent assemblies have safe grounding

Refrigeration System

- Deeply optimized refrigeration system, famous brand of compressor and major components, better refrigeration performance

User-Friendly Design

- Humanized design of computer control mode, intelligent without anxiety, adjustment free
- High performance insulation layer with better thermal insulation effect
- Self-evaporation of condensate water, humanized design of safety door lock etc

The Haier laboratory refrigerator you obtained is probably not exactly the same as illustrated in the User's Manual due to continuous improvement of product, we regret for this. Content of this instruction is subject to alternation without prior notice.

Product Feature	1
Content	2
Safety Precautions	3
Precautions for Use	6
Product Installation	7
Component Names•Control Panel.....	11
Application method	12
Cleaning and Maintenance.....	14
FAQ	15
Refrigeration Schematic&Circuit Diagram	16
Specification	18

Packing List

Name	HLR-198F	HLR-310F
Operation Manual	1	1
Factory inspection report	1	1
Calibration certificate	1	1
Key	2	2
Through hole peg	1	1
Plastic bag	1	1
Glass shelf	4	4
Handle	/	1
Handle Cover	/	2

Specification

Name	Laboratory Refrigerator	
Model	HLR-198F	HLR-310F
Exterior dimension (W×D×H)(mm)	530×570×1530	605×598×1840
Interior dimensions(W×D×H)(mm)	455×445×900	560×500×1290
Effective volume	198L	310L
Door	Foaming door	Foaming door
Insulation	CFC-Free foamed-in-place urethane	
Compressor	High Quality Hermetically sealed compressor	
Shelf/Loading of each shelf	Glass shelf/≤30kg	
Refrigerating Method	Forced-air cooling circulation	
Exterior / Interior	Spray coated steel plate / PS plate	
Condenser/Evaporimeter	Wire and tube type / plate type	
Temperature Control	Microprocessor controlled	
Refrigerant	R600a 33g	R600a 76g
Lamp	LED 3W	LED 3W
Net weight	57kg	72kg
Setting temperature range	3°C ~16°C	3°C ~16°C
Voltage	220V-240V ~/50Hz	220V-240V ~/50Hz
Input power	90W	150W
Anti-shock Safety Classification	I	I
Climate type	4	4
Noise Level(Lp)	37dB(A)	39 dB(A)
Foaming Agent	CP/IP	CP/IP
Alarm system	Hi-low temperature alarm, sensor error alarm, door ajar alarm	
Power failure alarm duration	/	
Production date /expected service life	On the barcode / 10 years	
Software release version	V4	

Note: Climate Type 4 means the temperature is +30°C ,the relative humidity is 55%. Technical information may vary from the appliance that you have just purchased due to technical improvements.

Dear users:

Thanks for your choice of Haier laboratory refrigerator, please make sure you have carefully read and observed the contents with following signs in the manual, for better understanding of this manual and better use of this product, so as to prevent personal injuries and refrigerator damage.

Safety labels



R600a



Fire



Hot surface



Overcurrent Protector



Ground

Safety Precautions



Actions or operations which are prohibited




Actions or operations which must be followed

Caution

- ! Close down the gas leaking valve and open the door and windows for ventilation in case of leakage of inflammable gas like coal gas etc., do not insert or pull out the power plug of the refrigerator, otherwise it may trigger an explosion and fire.
- ! Only the professional technicians or after-sale service men can install this refrigerator. Otherwise it may result in an electric shock or fire.
- ! Make sure to place the refrigerator firmly on a solid and flat ground. If the ground is not stable or it is not properly placed, it will cause overturn of the refrigerator or personnel injury.
- ! Please use the dedicated power supply indicated on the nameplate of the refrigerator, or otherwise, it may cause a fire or electric shock.
- ! If the service voltage is lower than 198V or higher than 242V, it is required to equip an automatic voltage regulator suitable for over 1000W motor load.
- ! If it is required to lengthen the power cord, the section area of the lengthen cord must not be less than 2mm² and the length shall not be longer than 3m. Otherwise, it may cause a fire or electric shock.
- ! If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.


- ❗ The power cord of this refrigerator is provided with a three-wire (earthing) plug, complying with the standard 10A three-wire (earthing) socket. Never cut or remove the earthing pin of the power cord in any case. Make sure that the power plug and socket is inserted tightly and reliably, otherwise it may result in a fire.
- ❗ Please use an earthed power supply socket for fear of electric shock.
- ⊘ If the power socket is not earthed, be sure to have the earth wire installed by a professional technician.
- ⊘ Do not use the refrigerator in the open air. When the refrigerator gets wet in the rainwater, it may cause leakage of electricity or electric shock.
- ⊘ Do not place the refrigerator in a damp site or a place where it may easily suffer from spraying water. Otherwise, it may cause leakage of electricity or electric shock due to degeneration of its insulation.
- ⊘ Do not pour water onto the refrigerator in a direct inclined way, otherwise it may cause an electric shock or a short circuit.
- ⊘ Do not place any vessel containing water or any heavy object on the refrigerator. If the object drops off, it may cause personal injury and the flowing water will degenerate the insulation and further cause leakage of electricity or electric shock.
- ⊘ Do not make the refrigerator earthed via a gas-pipe, power supply conduit, telephone line or lightning rod. The above earthing will cause an electric shock or other dangers.
- ❗ Do not contact any electric parts or any switches such as power plug and so forth with a wet hand, or otherwise it may cause an electric shock.
- ❗ When pulling out a plug from the power socket, hold the power plug firmly but do not pull the wire of the power plug. Pulling the wire with hand may cause an electric shock or lead to a fire due to short circuit.
- ⊘ If the refrigerator runs out of order, please pull out the power plug. Continuous running in an abnormal condition may cause an electric shock or fire.
- ❗ User must not dismantle, repair or refit the refrigerator by itself. Otherwise, it may cause a fire or personal injury due to improper operation.
- ❗ Before conducting any repair or maintenance of the refrigerator, be sure to disconnect the power of the refrigerator for fear of electric shock or personal injury .
- ❗ Make sure not to suck in medicine or suspended particles inside and surrounding the refrigerator in time of repair and maintenance, otherwise, it may bring hurt to your health.
- ❗ When storing toxic, hazardous or radioactive articles, please use the refrigerator in a safety zone.
- ❗ Improper use may bring hurt to human health or environment.
- ❗ If the refrigerator is left unused for a long time in an unattended area, make sure that children will not approach the refrigerator and the refrigerator door will not be closed completely.
- ❗ Disposal of discarded refrigerator shall be conducted by the relevant personnel. Dismantle the door to prevent occurrence of accidents such as suffocation.

Circuit Diagram



Refrigeration Schematic&Circuit Diagram

Refrigeration Schematic



Warning

- ⊘ Do not set off hazardous articles that are inflammable, explosive or volatilizable in the refrigerator, nor use the flammable spraying agent in the vicinity of the refrigerator, or otherwise, it may trigger an explosion or fire.
- ⊘ Do not store explosive substances such as aerosol cans with a flammable propellant in this appliance.
- ⊘ Do not place the packing plastic bags at the locations where children can easily take as plastic bags may cause occurrence of suffocation accident.
- ⊘ Do not climb up to the refrigerator or place articles on the refrigerator, otherwise it may cause personal injury or damage of refrigerator due to overturn of the refrigerator.
- ⊘ Do not insert any metal objects like iron nails, iron-wire into any orifice and gap or any air vent used for internal air circulation of the refrigerator, otherwise, it may cause an electric shock or injury due to contact of the above objects with the moving parts.
- ! When restarting the refrigerator after a power failure or power-off, it is required to check the setting of the refrigerator. Change of setting may spoil the articles stored.
- ! Once the power of the refrigerator is cut off, wait for over 5 minutes before it is reconnected so as not to damage the compressor or the system.
- ! Put on your gloves at time of maintenance so as not to bump the sharp edges or corners, resulting in personal injury.
- ! Close the door of the refrigerator with your hand holding the handle so that your fingers will not be pinched by the door.
- ! The inclination angle shall be no greater than 45 ° when handling the refrigerator.
- ⊘ When handling the refrigerator, be careful not to trip over it, preventing damage to the refrigerator or personal injury.
- ⊘ Do not pull or carry the equipment by the door handle, preventing damage to the refrigerator or personal injury.
- ! - WARNING:Keep clear of obstruction all ventilation openings in the appliance enclosure or in the structure for building-in.
- ! - WARNING:Do not use mechanical devices or other means to accelerate the defrosting process, other than those recommended by the manufacturer.
- ! - WARNING:Do not damage the refrigerant circuit.
- ! - WARNING:Do not use electrical appliances inside the storage compartments of the appliance, unless they are of the type recommended by the manufacturer.

- Product structure and composition: The product adopts a refrigeration system attached to the thermal insulation box which is microcomputer controlled with air cooling design, and a rack type design that can be adjusted at discretion, and an illuminating lamp is provided in its internal.
- Before putting the articles into the refrigerator, make sure firstly that the design temperature is reached inside the refrigerator, then put in the articles in batches. The articles put in every time shall not exceed 1/3 of the internal capacity so as to prevent temperature increase.
- The indicated temperature value of the refrigerator is the value indicated inside the refrigerator at the temperature sensing probe. Occasionally the indicated temperature has a certain difference with the actual temperature in the central part of the refrigerator, but it will gradually approach to the true temperature.
- Use the diluted mild detergent to clean the refrigerator. Do not use brushes, acid, gasoline, soap powder, polishing powder or hot water to clean the refrigerator as the above materials may damage the painting surface as well as the plastic and rubber parts and components. Take particular care not to use volatile solvent such as gasoline to wipe plastic and rubber parts and components.
- Cut off the power of the refrigerator when it is not in service for a long time.
- Every time when putting in and taking out the articles, please try to reduce the door opening time so as not to cause larger fluctuations of the temperature and humidity inside the refrigerator.
- After opening the door, the temperature inside the refrigerator will rise steeply in a short time, this is normal and the temperature will restore within one hour after the door is closed.



Meaning of crossedout wheeled dustbin:

Do not dispose of electrical appliances as unsorted municipal waste, use separate collection facilities. Contact you local government for information regarding the collection systems available. If electrical appliances are disposed of in landfills or dumps, hazardous substances can leak into the groundwater and get into the food chain, damaging your health and well-being.



If you have any questions about the operation of the refrigerator, please refer to the table frequent asked questions as follows. Call Haier technical support if you still have questions. Do not attempt to maintain or dismantle the unit by yourselves.

Fault	Troubleshooting
The refrigerator does not work	Inspect the power supply to make sure it meets therequirement
	Inspect the connection between the power plug and the socket
	Check the power cord for any obvious damage
	Whether the voltage is too low
Refrigeration effects are not apparent, temperature exceeds the standard	The unit is loaded with too much warm sample and product
	There is a lack of space between stored samples
	There might be a direct sunlight or other heat radiation energy on the refrigerator
	The door is opened too frequently
	Ambient temperature is too high
	Air duct is blocked
Unit seems to emit too much noise.	Check the installation of the unit to make sure the unit does sit on a solid floor without vibration
	Part of the refrigerator leans against a wall
	As a reference, the published sound data is obtained at specific laboratory condition. It is normal that the actual sound level in the field differs due to subtle installation and operation conditions
Alarm light flashes and alarm buzzer sounds	Warm products have been placed into the unit recently and the refrigerator has not stabilized yet. The alarm condition will be automatically corrected once the temperature reaches the set value
	The door is not closed properly
	The unit lost power recently and it is in the process of cooling down
	Ambient temperature might exceed the designed range

Component Cleaning



Warning

- In order to prevent an electric shock or personal injury, be sure to cut off the power of the refrigerator before conducting any repair to the refrigerator.
- Make sure not to suck medicine or suspended particles around the storage box when maintaining the refrigerator, otherwise, it will hurt your health.

Cleaning refrigerator

- Clean the refrigerator once a month. Regular cleaning can keep a completely new appearance of the refrigerator.
- Use a dry piece of cloth to wipe off the small amount of dust accumulated on the refrigerator's housing and inner chamber and all the accessories as well. If the refrigerator is very dirty, use a piece of cloth dipped with mild detergent to clean off the dirt, and use a piece of wet cloth to wipe the residual detergent, then wipe it with a dry piece of cloth.
- Do not pour water onto the refrigerator housing or into the storage box, otherwise, the electric appliance may be damaged.
- The compressor and other machinery parts are in completely sealed state, there is no need to lubricate them.

Replacing the illuminating lamp

The LED lamp is mounted in the upper front part of the refrigerator, exercise cautions when replacing the lamp:

- Unplug power plug;
- Remove the safety cover of the LED lamp;
- Take out the LED lamp;
- After changing with a new LED lamp, put it back to its original position;
- Turn on the power.



Caution


The new LED lamp must be the same gauge of the original.

Stopping refrigerator

- Cut off the refrigerator power if the refrigerator is not in service for a long time.
- Open the refrigerator's door and take out the inner plate glass shelf.
- Make thorough cleaning of the refrigerator.
- Clean the plate glass shelves.
- Wait till the Refrigerator and the plate glass shelves are dried in the air, and replace the plate glass shelves in the refrigerator.
- Close the door of the refrigerator and cover it with a plastic bag for sealing up.

Installation environment

- Environmental temperature: 16°C to 32°C, the optimal temperature is 18°C to 25°C, the air conditioning system shall be used when necessary.
- Ambient humidity: below 85% Rh.
- Avoid large quantities of dust.
- Avoid mechanical sway or vibration.
- The altitude of refrigerator's working position: lower than 2000m.
- Input voltage: within the range of 220V±10%.



Caution

- As the refrigerator is sensitive to the environmental temperature, it can not operate normally if it is installed in an environment other than the above. Please use it after improving the environment.
- It is prohibited to install the refrigerator in the open air environment. When the refrigerator gets wet in the rainwater, it may cause leakage of electricity or electric shock accident.

Installation site

For normal operation and optimum performance level of the refrigerator, its installation place shall conform to the following conditions:

- It can not be installed in a narrow, small and airtight space, the door frame of the room for placing it shall not be less than and lower than this product, and shall at least guarantee its normal passing in and out so as to avoid any maintenance difficulty and failure of in-time repair in occurrence of machine fault, causing spoilage to the stored articles.
- The ground at the installation place shall be solid and flat.
- It shall be well-ventilated without direct sunshine.
- Do not share a socket with other equipment, the plug and socket shall be well connected.
- Do not distort nor stress the power cord.
- If it is required to lengthen the power cord, the section area of the lengthened wire shall not be less than 2mm² and the length shall not be longer than 3m.
- Check the operating voltage before use, at the area where the voltage is not stable, use of a voltage regulator suitable for the motor load shall be considered for voltage stabilization. So that the normal input voltage is stabilized at 220V±10%, the power of the voltage regulator is greater than 1000W.
- The refrigerator shall be guaranteed with reliable earthing.
- If the power socket has earth wire, check if the earthing is good before use.
- If the socket is not furnished with an earth wire, be sure to install one by the professional engineering and technical personnel.
- Kept away from the radiated area and avoid the use of radiation-sensitive devices at its periphery.




Warning

- Do not make refrigerator earthing via gas piping, water supply pipe, telephone line or lightning rod that may easily cause an electric shock.
- After installation, the power plug must be accessible to facilitate unplugging of the power cord in emergency. No articles shall block out the air vent of the refrigerator.

Preparation before use

1. Take off the packing material and the packaging tape

Take off all packing materials and packaging tapes for transportation.


 Caution keep the plastic bag away from the children.

2. Check of accompanying accessories

Please check the box contents as per the packing list. If there is any mistake, please contact the aftersales department timely.

3. Storage condition

At least a 10cm gap shall be left around the storage box, to ensure the well air ventilation and to facilitate the heat radiation.

 Caution Sufficient space shall be kept at the engine-room grilling, to facilitate maintenance and ventilation.

4. Adjustment of leveling legs


Please use a wrench to turn the horizontal leveling legs clockwise so that the horizontal leveling legs are extended outwards and supported on the ground. Make sure that the refrigerator is not movable in time of use.



5. Standing

Do not power on the refrigerator firstly after leveling and cleaning. Let it stand still for over 24 hours before power it on so as to ensure normal running of the refrigerator.

6. Laying of through hole peg

There is a through hole peg placed in the information bag, place the through hole peg in the water outlet when using the refrigerator for the first time. In service course of the refrigerator, make sure that the water outlet is unblocked so that the thaw dripping flows to the water disposal pan inside the refrigerator via the water outlet, in case of clogging, just take out the through hole peg from the water outlet and replace it back after cleaning.

 Caution The through hole peg can not be used as a tool for clearing up the water outlet, it is placed in the water outlet only for preventing the water outlet from clogging.



● Fault display

This indicator has only one sensor fault display, in occurrence of a fault found with the sensor, the window displays EE and gives alarm, the refrigerator can still refrigerate in failure safe mode in a short time, but it is required to divert the articles stored to the other sound refrigerators as soon as possible and promptly contact the after-sale service department so as not to cause loss for you.

● Hi-low temperature alarm

In running process of the refrigerator, it will alarm if the temperature inside the box exceeds the hi-low temperature alarm limit, and the alarm indicator will flicker and buzzer beeps at the same time, the beeps can be cancelled by pressing the "Alarm" key, but the Alarm indicator will continue flickering until the temperature restores to the alarm limit.

● Query of alarm temperature

Press "Alarm" key and "+" key simultaneously to query the high temperature alarm limit, release and return to the box temperature display.

Press "Alarm" key and "-" key simultaneously to query the low temperature alarm limit, release and return to the box temperature display.

● Query of the recent max. & min. actual temperature values inside the box

Press "Set" key and "+" key simultaneously to query recent max. actual temperature value, release and return to display the temperature inside the box.

Press "Set" key and "-" key simultaneously to query recent min. actual temperature value, release and return to display the temperature inside the box.


● Adjustment of alarm limit

Set up the high temperature alarm limit (HA) and the low temperature alarm limit (LA) with the method below:

Keep pressing the "Alarm" key for over 10s, the code HA appears in the display window, press the "Set" key once (quick), the original setting value of HA is displayed and flickering, adjust the setting value by pressing the up key "+" or down key "-", the setting value changes for 1°C for every press with the adjusting range of no higher than the temperature setting value of +6°C. Press the "Alarm" key to exit and return to HA display of the last layer (one layer return for each pressing of the "Alarm" key, till it returns to the temperature display of the box). Choose another parameter LA by pressing up key "+" or down key "-". The method for setting LA is same as above, its adjusting range is not lower than the box temperature setting value of -6°C.

Temperature indicator

The front control panel of the refrigerator is equipped with a temperature indicator that facilitates adjustment of the box temperature inside the refrigerator. For first use, the refrigerator shall run at least for over 30 minutes before it reaches the stable state, do not make any adjustment before it is stabilized. Schematic diagram of temperature indicator:



●Unlocking operation

When no operation is made by the user within 20s, the temperature setting, internal parameter setting and hi-low temperature alarm setting key are locked, the functions of the "ALARM " key to cancel the warning sound, the "Light" key to turn on, turn off the lamp, the Max. and Min. temperature query, hi-low temperature alarm limit query are still effective, when it is required to unlock, press "+" key, the numerical value at inside temperature display area flickering 01, press "+"key or "-"key again to input the set password value, then press "Set" key to unlock, after successful unlocking, the buzzer beeps once, the box temperature display area normally indicates the temperature(if the password is wrong, the display area continues flickering of password value and will exit if no operation is made over 5s);

●Setting of password value

The Default unlocking password is "06", after unlocking, and press at the same time the "Set" and "Alarm" key for 5s, the display screen displays 06, then regulate the password value by pressing "+"and "-"keys, the password value can selected among 05, 06, 07.....29,30. After setting the password value, press "Set" key to exit or automatically enter the lock-out state if no operation is made within 5s, the set password value is effective.

Moreover, in course of internal parameter setting and hi-low temperature alarm setting, it will automatically exit and indicate again the box temperature value if no operation is made within 10s.

●Temperature regulation

The preset box control temperature of the refrigerator before factory delivery is 5°C .

To set up the temperature inside the box, firstly conduct unlocking operation. Press again the "Set" key and quickly release, the display window displays the original setting value and flickering, when the setting value is flickering, adjust the setting value by pressing up key "+"or down key "-", the setting value changes 1°C if it is pressed once, and it will automatically exit and redisplay the box temperature value (no flickering) if no operation is made within 10s. After running for a period of time, the refrigerator box temperature will reach the set temperature.

Initial Power-on

Please observe the following rules when conducting initial start-up and continuous running:

Connect the power cord to the dedicated socket of proper gauge when the refrigerator is empty, make sure the power supply is 220V/50Hz.

This refrigerator is preset for running at 5°C before factory delivery.

The sound alarm will ring after power-on and this is normal. At this moment, press the "Alarm" key on the control panel to cancel the alarm beep. The alarm indicator keeps flickering till the temperature sensor reaches the temperature range required.

The temperature can be stabilized at the set temperature after the refrigerator has been running for a period of time.

Start putting articles gradually into the refrigerator after completing a thorough inspection of the refrigerator.

- ❗ A person shall be specially assigned for daily check and record of the product operating conditions, in case the temperature inside the refrigerator is on the high side or on the low side, just transfer the articles to the other storage boxes till the fault is removed and then replace back the articles.
- ❗ The indicated temperature of this product may have a certain difference with the actual temperature inside the boxes due to refrigeration inertia, this is normal.
- ❗ Do not put any articles in the space between the bottom of the refrigerator's internal bladder and the bottom rack for fear of air duct clogging and affecting the temperature uniformity inside the boxes.
- ⊘ All the refrigerators are of storage equipment, and it is strictly forbidden to put excessive articles that are relatively too hot in one go, this will cause long time of running of the compressor without stop, slow drop of temperature, thus affecting service life of the compressor, the articles must be put in batches so that the temperature drops in steps till the required temperature is reached.

Operation of over-current protector

1. Mounting position: This device is mounted on the backside of the product, and there is a special warning sticker to mark it.
2. Working principle: In occurrence of any abnormalities found with the interior circuit of the product that exceed the protection limit of the over-current protector, this device will automatically spring up, cut off the connection with the external circuit and play the role of protecting the entire equipment circuit; at time of reuse, it is required to manually push down the device and the product is powered on for running.

Operation after power failure

The refrigerator has memory function to the setting values, after re-electrified following a power failure, the refrigerator will continue running as per the parameters set up before the last power failure.



Caution

- Once the power of the refrigerator is cut off, wait for over 5 minutes before it is reconnected so as not to damage the compressor or the system.
- Pull out the power plug when the refrigerator is not in service for a long time so as to prevent electric shock, leakage of electricity or fire due to aging of the power cord.
- If the refrigerator is left unused for a long time in an unattended area, make sure that children will not approach the refrigerator and the refrigerator door can not be closed completely.

Component Names



Control panel

