## THERMO-HYGROMETER WITH DEW POINT

ET-931



## **PRODUCT DESCRIPTION**

This thermo-hygrometer with dew point is a compact, easy-to-use, robust instrument for fast, repeatable measurements of relative humidity, temperature and dew point. It is ideal for single handed operation when taking measurements in air stream. Suitable for monitoring air conditioning and heating system ducts, controlled environments, storage areas, etc.

- -20° to 70°C x 0.1°
- 0% to 100%RH x 0.1%
- Displays temperature in °C or °F
- Dew point measurement
- Simultaneous display of humidity and temperature readings
- 35mm hi-contrast LCD display with backlight
- Data hold freezes displayed measurements
- Min/max memory since power on
- Low battery indication
- Auto power off after approximately 15 minutes
- 2 year warranty
- Supplied with soft carry pouch and battery

Lenneal	SPECIFICATION		Dew Point
	Temperature	Humidity	Dew Point
Range	-20° to 70°C	0% to 100%RH	-20° to 70°C
Resolution	0.1°C	0.1% RH	0.1°C
Accuracy	±1°C	±4%RH (0 to 20%RH) ±3%RH (20 to 40%RH) ±2.5%RH (40 to 60%RH) ±3%RH (60 to 80%RH) ±4%RH (80 to 100%RH)	±1°C
Power	1 x 9V PP3 alkaline battery ( <b>LR-61</b> )		
Dimensions	192 x 62 x 32mm		
Weight	151g		



Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

## www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.