

Biometra TAdvanced PCR Thermal Cycler



Technical Data

Biometra TAdvanced

General

- Stand-alone control by 7" color touchscreen or remote control by cycler network
- Whisper Quiet with max. 45 dB
- Small footprint and minimal clearance zone
- Different quick exchange sample blocks for various sample volumina, with or without gradient function (Linear Gradient Tool LGR)
- HPSL technology for ideal constant contact pressure independent of the used consumable
- Suitable for low-profile and high-profile plastic with or without skirt, as well for semi-skirt

Thermal block

	96/96 G	96 S/96 SG	60/60 G	384/384 G
Sample block	Aluminum, special alloy	Silver, gold coating	Aluminum, special alloy	Aluminum, special alloy
Block capacity	96 x 0.2 ml tubes, 96 well microplate or 8 well strips	96 x 0.2 ml tubes, 96 well microplate or 8 well strips	60 x 0.5 ml tubes	384 well microplate
Proposed sample volume	5 - 50 µl	5 - 100 µl	20 - 150 µl	5 - 25 µl
Max. heating ¹	6.0 °C/s	8.0 °C/s	6.0 °C/s	4.0 °C/s
Average heating ¹	5.5 °C/s	7.0 °C/s	5.5 °C/s	3.8 °C/s
Max. cooling ¹	4.0 °C/s	5.5 °C/s	4.0 °C/s	2.0 °C/s
Average cooling ¹	3.5 °C/s	4.5 °C/s	3.5 °C/s	1.7 °C/s
Temperature uniformity ²	95 °C ± 0.60 °C 70 °C ± 0.30 °C 55 °C ± 0.20 °C	95 °C ± 0.50 °C 70 °C ± 0.25 °C 55 °C ± 0.15 °C	95 °C ± 0.60 °C 70 °C ± 0.30 °C 55 °C ± 0.20 °C	95 °C ± 0.50 °C 70 °C ± 0.25 °C 55 °C ± 0.15 °C
Gradient ³	Linear Gradient Tool	Linear Gradient Tool	Linear Gradient Tool	Linear Gradient Tool
Max./Min. gradient ³	30 °C/0.1 °C	40 °C/0.1 °C	30 °C/0.1 °C	24 °C/0.1 °C
Adjustable gradient range ³	12 rows 20 °C to 99 °C	12 rows 4 °C to 99 °C	12 rows 20 °C to 99 °C	12 rows 20 °C to 99 °C

¹ measured at cavity wall of the block

² after 15 sec

³ only for gradient models (G)

Technical Data

Biometra TAdvanced

	Twin 48/48 G ⁵	Twin 30	Twin combi
Sample block	Aluminum, special alloy	Aluminum, special alloy	Aluminum, special alloy
Block capacity	2 x 48 x 0.2 ml tubes/ 2 x 48-well microplates/ 2 x 6 x 8-well strips, 0.2 ml	2 x 30 x 0.5 ml tubes	2 x 48 x 0.2 ml tubes/ 2 x 48-well microplates/ 2 x 6 x 8-well strips, 0.2 ml/ 2 x 18 ⁴ x 0.5 ml tubes
Max. proposed sample volume	5 - 70 µl	20 - 200 µl	20 - 140 µl (0.5 ml), 5 - 70 µl (0.2 ml)
Max. heating ¹	5.2 °C/s	4.2 °C/s	3.1 °C/s
Average heating ¹	5.1 °C/s	4.1 °C/s	3.0 °C/s
Max. cooling ¹	4.1 °C/s	3.3 °C/s	2.3 °C/s
Average cooling ¹	4.0 °C/s	3.1 °C/s	2.2 °C/s
Temperature uniformity ²	95 °C ± 0.60 °C 70 °C ± 0.30 °C 55 °C ± 0.20 °C	95 °C ± 0.60 °C 70 °C ± 0.30 °C 55 °C ± 0.20 °C	95 °C ± 0.60 °C 70 °C ± 0.25 °C 55 °C ± 0.20 °C
Gradient ³	Linear Gradient Tool ⁵	-	-
Max./Min. gradient ³	20 °C/0.1 °C ⁵	-	-
Adjustable gradient range ³	8 rows 20 °C to 99 °C ⁵	-	-

¹ measured at cavity wall of the block

² after 15 sec

³ only for gradient models (G)

⁴ The capacity is increased to 35 x 0.5 ml tubes for tubes with small caps

⁵ Only 1 block of the twin-block includes the gradient function.

Block exchange	Yes
Number of blocks	12
Tempering method	Peltier elements
Standby temperature	Yes, down to 4 °C
Temperature control mode	Block control
Adjustable temperature range	3 °C to 99 °C
Temperature control accuracy	± 0.1 °C

Technical Data

Biometra TAdvanced

Heated lid

Heated lid	High-Precision Smart Lid (HPSL)
Lid temperature	30 °C to 110 °C
Contact pressure	Approx. 8 kg, manual with integrated slip clutch for constant contact pressure independent from the used consumables

Control

Control	Stand-alone or remote control via tablet PC
Control and analysis software	Remote Control App
Operating system	App for iOS or Android
Minimum requirements remote device	iOS 8.0 or Android 4.4 or newer (API 19)
Minimum requirements cycler	Software version V1.43 - V1.44
Language	English, German, Chinese
Display	7" Color touchscreen
Export function	Yes
Power fail function	Yes
Quick start function	User-specific quick start
Time inc	1 to 240 s/cycle
Temperature inc/dec	±0.1 to 20 °C/cycle
Memory capacity	350 programs à 6 steps in up to 90 user directories
Features	<ul style="list-style-type: none">▪ Extended Self Test▪ Graphical or spreadsheet programming▪ Multip-step programming▪ Incubation mode▪ Protocol templates▪ Program preview

Dimensions

Weight netto	Approx. 15 kg
Dimensions (W x D x H)	277 mm x 457 mm x 264 mm
Required clearance zone	10 cm behind rear side of the device. When operating several units side by side, an additional 10 cm between the units.

Technical Data

Biometra TAdvanced

Additional technical data

Interface	<ul style="list-style-type: none">▪ USB-A (front side): connection of an USB flash drive▪ Ethernet (back side): connection to a network
Fuses	2x T 10A H 250 V
Power supply	100 V, 115 V oder 230 V ± 10 %, 50 – 60 Hz
Power consumption	Max. 850 W
Noise emission	Max. 45 dBA
Operation conditions	15 °C to 35 °C, 70 % humidity, max. 2.000 m NN, overvoltage category II, pollution degree 2, IP20
Warranty	2 years warranty o the device system

This document is true and correct at the time of publication; the information within is subject to change. Other documents may supersede this document, including technical modifications and corrections.

Content may be used without written permission but with citation of source. © Analytik Jena AG



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.