

# Iso Electric Focusing

Equipped with rehydration and focusing trays, this system has been optimised to perform firstdimension isoelectric

focusing (IEF) with IPG (immobilised pH gradient) strips and IEF gels quickly, easily and reproducibly





- For IPG strips and IEF gels
- Large cooling platform area
- 'Pick-and-Place' adjustable electrodes
- Focusing tray for a maximum twelve IPG strips
- Rehydration tray also included

Equipped with rehydration and focusing trays, the Cleaver Scientific IEF system has been optimised to perform first-dimension isoelectric focusing (IEF) with IPG (immobilised pH gradient) strips quickly, easily and reproducibly. It can also be used with precast IEF Gels.

An ideal entry-level system for both experienced and occasional IEF users, the unit is versatile enough to meet the needs of laboratories with increased throughput requirements as well as first time users.

### **HIGH CAPACITY**

Its high-capacity focusing tray accommodates up to twelve IPG strips. Adjustable 'pick-and-place' electrodes clip conveniently anywhere within the focusing tray to resolve IPG strips 7-24cm in length and are colourcoded to prevent polarity reversal. The Electrode frame clips directly on to the cooling plate and includes adjustable electrodes to run horizontal precast IEF and PAGE gels.


A cooling plate, manufactured from a special grade ceramic in a large 26x26cm surface area, facilitates effective heat dissipation and control, particularly during high voltage IEF techniques. An optional, but recommended, recirculating chiller connects quickly and easily to the cooling plate to maintain optimal operating temperatures for IPG strips and precast gels.

### REHYDRATION

The Rehydration tray allows convenient transfer of IPG strips to the focusing tray without time-consuming removal of residual rehydration buffer and also enables the focusing tray to remain permanently in use for IEF to maximise throughput and provides useful storage at -20°C for focused strips before second-dimension runs.

For those requiring a power supply, the Consort EV3330, 3000V, 300mA, 300W enables desired Volt-hours for focusing to be attained faster at maximum voltage.

### **Isoelectric Focusing**



### **IEF COMPONENTS**

2. Adjustable 'pick-and-place' electrodes

3. Ceramic cooling plate with snap-lock

1. Focusing Tray

connectors

- 4. Rehydration tray (not shown)
- 5. Electrode frame for horizontal precast gels
  - Shrouded 2mm high voltage cables (not shown)

Typical R		J Condit	ions				
7cm IPG St	rip						
IEF STEP	1	2	3	4	5	6	
Voltage (V)	150	300	600	1500	3000	300	
TIME (H)	0.5	0.5	0.5	0.5	2.5	<20	
Volt-hours	75	150	300	750	7500	-	
18cm IPG Strip							
IEF Step	1	2	3	4	5		
Voltage (V)	300	600	1500	3000	300		
Time (h)	0.5	1	1	12	<20		
Volt-hours	150	600	1500	36000	-		
	IPG Strip Length						
Tray Spe	cificati	ons	7cm	11cm	18cm	24cm	
Focusing Tray							
Electrode Distance			6.5см	10.2см	17.1см	22.7см	

Focusing Tray				
Electrode Distance	6.5см	10.2см	17.1см	22.7см
Maximum Strip Length Accommodated	25.3см	25.3см	25.3см	25.3см
IPG Strip Length	7см	11см	18см	24см
Rehydration Tray				
MAXIMUM STRIP LENGTH ACCOMMODATED	24см	24см	24см	24см
RECOMMENDED VOLUME FOR STRIP REHYDRATION	3.5ML	6ML	8.0ml	12.0ML

ORDERING INFORMATION						
Cat. No.	Description					
CSL-IEF	Flatbed IEF system for IPG strips and gels, with focusing and rehyd	ration trays				
CSL-CHILLER	Chiller system, -20 to 100°C, including insulated tubing & clips	CSL-IEFFRME	Replacement electrode frame			
CSL-IEF-KIT	1-D Combination Package, includes IEF, CHILLER and EV3330	CSL-RHYDTRY	Rehydration Tray			
CSL-IEFPOS	Replacement positive electrode	CSL-FOCUSTRAY	' Focusing tray with adjustable electrodes			
CSL-IEFNEG	Replacement negative electrode	EV3330	Consort 3000V, 300mA, 300W power supply			
CSL-IEFPLT	Replacement Glass platform					



Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

## www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.