



Bottle Probe Bullet™ Probe Vaccine Probe Plastic Bottle Probe



Platinum RTD sensors, Stainless-steel 316 Probe



98768-57

Traceable® Excursion-Trac™ Datalogging Refrigerator/Freezer Thermometers

Datalogging thermometer with user-defined time intervals

- User-defined time intervals, MIN/MAX and current conditions displayed on LCD, and °F/°C switchable
- Stores up to 10 unique alarm events
- Meets current CDC requirements for vaccine storage and monitoring
- Rolling memory structure, maintains most recent 525,600 temperature observations
- Hassle-free retrieval of data—unit can remain in use while downloading/analyzing data
- Recorded data (CSV file) may be transferred from thermometer to PC or Mac using a USB flash drive—no additional software needed
- Smart-Alarm™ features a visual/audible alarm that continues to alarm even if the unit returns to non-alarm conditions
- 98768-53 and 98768-54 are ideal for monitoring ultra-low temperature freezers and include a PTFE cable
- Status indicators—low battery, memory full, USB data transfer, active alarm state
- Supplied: stand, Velcro®, magnetic strips, wall mount, batteries, Traceable® Certificate

Cat. No.	Temperature Range	Resolution	Accuracy	Probe			
94460-07	-50.00 to 70.00°C (-58.00 to 158.00°F)	0.01°	±0.25°C	1 bottle (patented)			
94460-09				2 bottles (patented)			
94460-11				1 Bullet™			
94460-14				2 Bullets™			
94460-18				1 bottle & 1 Bullet™			
94460-16				1 stainless-steel			
94460-17				2 stainless-steel			
98767-63				1 vaccine bottle (5ml)			
98767-64				2 vaccine bottles (5ml)			
98767-67				1 plastic bottle			
98767-68				2 plastic bottles			
98768-53				-90.00 to 105.00°C (-130.00 to 221.00°F)	0.01°	±0.2°C	Platinum RTD sensors, 1 stainless-steel 316 Probe
98768-54					0.01°	±0.2°C	Platinum RTD sensors, 2 stainless-steel 316 Probes

Traceable® LN2 Thermometer

Datalogging thermometer with user-defined time intervals

- Best for monitoring your cryo needs for sensitive biologicals
- Hassle-free retrieval of data—unit can remain in use while downloading/analyzing data
- Recorded data (CSV file) may be transferred from thermometer to PC or Mac using a USB flash drive—no additional software needed
- Smart-Alarm™ features a visual/audible alarm that continues to alarm even if the unit returns to non-alarm conditions
- Durable platinum RTD sensor, 316 stainless-steel 316 with 3 m cable
- Multiple calibration points (-196°C, -80°C, 0°C and 100°C)

Cat. No.	Temperature Range	Resolution	Accuracy	Data Overwrite	Memory	Probe
Excursion-Trac™						
98768-57	-200.00 to 105.00°C (-328.00 to 221.00°F)	0.01°	±0.25°C	Yes	525,600 data points	Platinum RTD sensors, 1 stainless-steel
98768-58						Platinum RTD sensors, 2 stainless-steel
Memory-Loc™						
98768-59	-200.00 to 105.00°C (-328.00 to 221.00°F)	0.01°	±0.25°C	No	1,051,200 data points	Platinum RTD sensors, 1 stainless-steel
98768-60						Platinum RTD sensors, 2 stainless-steel



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.