



## Cole-Parmer® VPS-200 Series Air Vacuum Pumps

- Compact size and integral handle make pumps easily transportable
- Economical vacuum pumps serve as a pressure or vacuum source with an excellent price-to-performance ratio
- Low-friction piston runs cool and quiet for a long service life with consistent performance
- 1-year warranty



Vacuum/Pressure Pump  
79202-00 | 79202-05

# Cole-Parmer VPS-200 Series Air Vacuum Pumps

This portable vacuum pump is designed for portability and versatility with a tough, lightweight plastic housing and integral carrying handle. The long-wearing motor delivers performance characteristics suitable for a wide range of applications. Wetted parts include glass-filled PA66, gas phase rubber, PTFE, TPU, and acetal.

**What's included:** 1.8 m (6 ft) cord with US standard plug on 115 VAC models. IEC socket with 1.8 m (6 ft) EU and UK mains lead with plug on 230 VAC models.

**NOTE:** Do not pump liquids or immerse pump. Avoid organic, basic and acidic vapors.



Vacuum Pump Station  
79202-30 | 79202-35

Free air capacity	Maximum vacuum	Maximum pressure*	Port connections	Motor	Operating conditions	Dimensions	Power	Item number
VPS-200 Air Diaphragm Vacuum/Pressure Pumps								
10.5 L/min (0.37 cfm)	541 mm Hg (21.3 in Hg)	33 psig (2.27 bar)	¼" hose barb	1/11.5 hp (65 W) shaded pole	0 to 40 °C (32 to 104 °F); 10 to 90% RH noncondensing	18.4 x 10.9 x 21.5 cm (7.2" x 4.3" x 8.5")	115 VAC, 60 Hz	<b>79202-00</b>
8.8 L/min (0.31 cfm)	541 mm Hg (21.3 in Hg)	33 psig (2.27 bar)	¼" hose barb	1/11.5 hp (65 W) shaded pole	0 to 40 °C (32 to 104 °F); 10 to 90% RH noncondensing	18.4 x 10.9 x 21.5 cm (7.2" x 4.3" x 8.5")	230 VAC, 50 Hz	<b>79202-05</b>
VPS-200 Air Diaphragm Vacuum/Pressure Pump Stations with Vacuum Gauge and Regulator Valve								
10.5 L/min (0.37 cfm)	541 mm Hg (21.3 in Hg)	33 psig (2.27 bar)	¼" hose barb	1/11.5 hp (65 W) shaded pole	0 to 40 °C (32 to 104 °F); 10 to 90% RH noncondensing	18.4 x 10.9 x 21.5 cm (7.2" x 4.3" x 8.5")	115 VAC, 60 Hz	<b>79202-30</b>
8.8 L/min (0.31 cfm)	541 mm Hg (21.3 in Hg)	33 psig (2.27 bar)	¼" hose barb	1/11.5 hp (65 W) shaded pole	0 to 40 °C (32 to 104 °F); 10 to 90% RH noncondensing	18.4 x 10.9 x 21.5 cm (7.2" x 4.3" x 8.5")	230 VAC, 50 Hz	<b>79202-35</b>

\*Intermittent duty: limit output to 33 psig – Continuous duty: limit output to 10 psig.



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.