

Cole-Parmer[®] Stuart[™] Shaking Incubator – SI-200D & SI-200D-L

- Incubator with shaker
- Integrated timer
- Digital display for temperature and speed
- Retractable platform for easy loading and unloading
- Optimised performance to minimise sample evaporation
- Communications enabled for external temperature measurement
- Comes in two sizes - 51 L and 115 L
- Three year warranty





Cole-Parmer® Stuart™ Shaking Incubator – SI-200D & SI-200D-L

The Cole-Parmer® Stuart™ SI-200D and SI-200D-L range of incubators, with integrated shakers, are ideal for cell culturing procedures, especially suspension culture applications.

The compact units feature a microprocessor controller and an LED control panel that allow independent control of speed and temperature, as well as a timer that can be set for any duration from 1 second to 9 days. Forced air circulation within the incubator ensures temperature uniformity, between +5°C and +60°C throughout the sample chamber. A retractable platform facilitates easier access to samples at the back of the incubators. Both models have a versatile clamping system, for common flask sizes - up to 1 L on the SI-200D and 2 L on the SI-200D-L. A wide range of stainless-steel accessory racks are also available for smaller sample tubes - 1.5ml, 15ml and 50ml. Accessory racks are held to the shaking platform by a Magnalock system, to ensure quick and easy coupling and de-coupling. The incubators feature smoked acrylic windows to allow easy visibility of the samples and the compact design ensures the units do not take up much space on the lab bench. The built-in USB connection with dedicated software allows long term temperature monitoring.

Technical Specification

Specification	SI-2000	SI-200D-L
Temperature range	Ambient +5 - 60°C	Ambient +5 - 60°C
Temperature display resolution	0.1°C	0.1°C
Temperature precision	± 0.5°C	± 0.5°C
Temperature fluctuation	± 0.5°C	± 0.5°C
Temperature variation	<0.5°C	<0.5°C
Speed range, rpm	30 to 300 rpm	30 to 300 rpm
Orbit diameter, mm	16	16
Platform size, mm	335 x 335	526 x 390
Capacity, L	51	115
Internal dimensions (w x d x h), mm	422 x 408 x 297	623 x 465 x 395
Maximum vessel height, mm	250	300
Maximum load, kg	10	10
Overall dimensions (w x d x h),mm	450 x 474 x 522	675 x 542 x 642
Net weight, kg	30	55
Heater power	250W	400W
Electrical supply	230V, 50Hz, 300W	230V, 50Hz, 450W

Ordering Information

Description	Ordering Number	Series No.	Model No.	Legacy Sku.
Incubator orbital shaker	79520-04	SI-200	SI-200D	SI500
Incubator orbital shaker 120V/60HZ	79520-00	SI-200	SI-200D-120	SI500/120/60
Incubator orbital shaker with IQOQ document	79520-06	SI-200	SI-200D	SI500/IQOQ
Incubator orbital shaker	79520-16	SI-200	SI-200D-L	SI600
Incubator orbital shaker 120V/60HZ 120V/60HZ	79520-14	SI-200	SI-200D-L-120	SI600/120V/60
Incubator orbital shaker with IQOQ document	72520-18	SI-200	SI-200D-L	SI600/IQOQ

Accessories

Description	Ordering Number	Series No.	Legacy Sku.
Tube rack, 1.5ml x 64 microtubes	79520-96	SI-200	SI500/1
Tube rack, 15ml x 25 centrifuge tubes	79520-97	SI-200	SI500/2
Tube rack, 50ml x 12 centrifuge tubes	79520-98	SI-200	SI500/3
Tube rack, 16ml x 30 universal containers	79520-99	SI-200	SI500/4



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.