

MX-T6-Pro

LCD Digital Tube Roller

Features

- LCD displays the speed and time
- Rocking & rolling at variable-speed
- Adjustable speed range from 10 to 70 rpm
- Six roller design for gentle and efficient rolling, and easy to clean
- DC brushless motor quiet and maintenance free
- Cold room and incubator compatible



LCD display



Timer



MX-T6-S

Standard tube roller

Features

- Adjustable speed range from 0 to 70 rpm
- Six roller design for gentle and efficient rolling, and is easy to clean

Applications

DLAB laboratory tube rollers provide a gentle and highly efficient rolling motions, deal for mixing blood samples, viscous substances and liquid-solid suspensions. Used in a variety of applications, such as the prevention of blood coagulation, immune precipitation, etc.

Specifications	MX-T6-Pro	MX-T6-S+
Amplitude	24mm	24mm
Motor type	Brushless DC motor	Brushless DC motor
Rocking motion	Rocking and rolling	Rocking and rolling
Max. load capacity	4kg	4kg
Number of rollers	6	6
Roller size[length]	280mm	280mm
Speed range	10-70rpm	0-70rpm
Speed display	LCD	Scale
Timer	Yes	-
Timer display	LCD	-
Time setting range	1-1199min	-
Operation mode	Continuous/timer	Continuous
Voltage,Frequency	100-240V,50/60Hz	100-240V,50/60Hz
Power	30W	25W
Dimension [D×W×H]	485×250×100mm	485×250×100mm
Weight	5.1kg	4.5kg
Permissible ambient temperature and humidity	5-40°C,80%RH	5-40°C,80%RH
Protection class	IP21	IP21



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed, please provide these to our sales team so that details can be confirmed.

