

# DM0506

## Low-speed Centrifuge



### Available adapters

#### A5P17 Cat. No.19500022

5mL adapter, Adapted to 13×75mm blood collection tube



#### A2P17 Cat. No.19500023

1.5/2mL Cryogenic Vials/ centrifuge tube adapter



## Features

- Speed range from 300-5000 rpm
- Set and displayed by RPM or G-force
- Two programs P1/P2, easy to start the procedure by one key
- Two deceleration speeds setting to meet different requirements
- Easy-to-read LCD display and sound alert
- Automatic lid-lock release after running
- Maintenance-free brushless DC motor

## Applications

DM0506 is widely used in the medical industry. Ideal for separation of serum, plasma, urine, fecal samples in biochemical & medical laboratories. It is an essential equipment of every clinical laboratory, blood bank, medical college and medical research institute.

Specifications	DM0506
Speed Range	300-5000rpm, increment:10rpm
Max. RCF	2600×g, increment: 10×g
Speed accuracy	±20rpm
Rotor type	6x15mL/10mL/7mL/1.5-5mL
Run Time	30sec-99min, HD (continuous running)
Display	LCD
Preloaded Program	P1/P2
Acceleration/Deceleration	1 ↑ 2 ↓
Safety Devices	Door interlock, Overspeed detector, Automatic internal diagnosis
Motor	Brushless DC motor
Power Requirements	Single-phase, 100V-240V, 50Hz/60Hz, 70W
Dimension[WxDxH]	300X240X180mm
Weight	5.2kg
Advanced features	Speed/RCF switch; sound-alert function





**Use the above details to contact us if this literature doesn't answer all your questions.**

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

**The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed, please provide these to our sales team so that details can be confirmed.**

