



HP500-Pro

LCD Digital Hotplate

Features

- LCD screen shows temperature, Max. temperature up to 500°C
- 10-inch glass ceramic work plate provides excellent chemical-resistant performance and most efficient heat transfer
- External temperature control is possible by connecting the temperature sensor (PT 1000) with an accuracy at $\pm 0.2^\circ\text{C}$
- The “HOT” warning will flash if the work plate temperature is above 50°C even when the hotplate is turned off
- Heating temperature: room temperature -500°C.
- Data connector : The SD card records the instrument's running data in real time.
- Timing function: the running time of the instrument can be set.

Specifications	HP500-Pro
Work plate Dimension [W x D]	254x254mm (10 inch)
Work plate material	Glass ceramic
Heating position	1
Heating temperature range	Room Temp.-500°C, increment 1°C
Temperature control accuracy	$\pm 1^\circ\text{C}$ (<100°C) $\pm 1\%$ (>100°C)
Safety temperature	540°C
Temperature,time display	LCD
Timer function	1min-99h59min
Temperature display accuracy	$\pm 0.1^\circ\text{C}$
External temperature sensor	PT1000($\pm 0.2^\circ\text{C}$)
"Hot" warning	50°C
Protection class	IP21
Power	1400W
Heating output	1350W
Voltage,Frequency	100-120/200-240V, 50/60Hz
Dimension[WxDxH]	328x424x138mm
Weight	7.2kg
Permissible ambient temperature and humidity	5-40°C, 80%RH



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed, please provide these to our sales team so that details can be confirmed.

