Glass Door: DLS700PG

Overview

Our intuitive range refrigerators feature built-in wireless monitoring software, enabling you to access the refrigerator's performance remotely.

Plus, our bespoke touchscreen controller, designed specifically for the end user with simple access to key information.



Key Features



Advanced Controller Easy to use touch screen controller, with no awkward buttons to press



Connected Wireless temperature monitoring built-in



Dual Temperature Probes

View your daily minimum and maximum temperatures in one touch



Battery Back-Up A/V alarms should your temperature stray or the door be left open



Antimicrobial Protection

Biocote® handle helping protect from microbes such as E. coli, Campylobacter, Salmonella and MRSA



Self-Closing Doors Fitted with self-closing hinges to help

avoid any temperature loss

DLS700PG - Product Specification

NeedDisplayGens Capacity Lites)A00Gens Capacity Lites)A00Unit Caronal With runn)R00Backer Mith runn)R00Backer Mith runn)R00Packer	Counter Top	
Net Capacity Clines)422Unit External Deptiform)000 (ext Fundle)Unit External Deptiform)000 (ext Fundle)Decked Wein (furm)800Pecked Neight Gam)900Pecked Neight Gam)900Pecked Neight Gam)2000Pecked Neight Gam)2000Pecked Neight Gam)600 (ext SubTampenture Range-200 (ext SubTampenture Range-200 (ext SubDoor TypeBight Hand FundleDoor TypeSub Sub Sub SubCapeabed Neight GamVes Careet SubDoor StellVes Careet SubOpen Door SentorVes Careet SubCakVes Careet SubPathele FeetSub Sub SubPathele FeetSub Sub SubPathele SubSubPathele Sub	Model	DLS700PG
Unit External Weith room200Unit External Height form800Decked Depth from800Packed Mith from90Packed Mith from90Packed Meight from90Part Parked90Parked Meight from90Parked Meight from90Parke	Gross Capacity (Litres)	700
Unit External Depth form)2040 (and handle)Unit External Height form)2040Packed Widt form)910Packed Weight Gaph910Packed Weight Gaph150Packed Weight Gaph150Packed Weight Gaph500 (acdista)0Temperature Range-20 (a fGExternal FinishPacked Meight GaphInternal Finish GambPacked Meight GaphType of PasiteN/ADoor TypeRolt Heid MingdDoor TypeRolt Heid MingdOpen Door DestilMainOpen Door SealVer / McYnorcolAdjustale FeetCasters MOpen Door SealVer / McYnorcolAdjustale FeetCasters MPart DestilVer / McYnorcolAdjustale FeetScientres MCasters MScientres MPart DestilVer / McYnorcolAdjustale FeetScientres MRott DestilVer / McYnorcolAdjustale FeetScientres MPart DestilVer / McYnorcolAdjustale FeetScientres MainPart DestilVer / McYnorcolRomo CastersNome Of Stell PositionsStell Top ScientresScientresNumber Of Stell PositionsScientresStell Top ScientresNome Of Scientres<	Net Capacity (Litres)	482
Valit Schemb Hight from)2040Packed Upit from)800Packed Upit from)200Packed Upit from)200Packed Weight from)800Packed Weight Gop)850Internal Dimensions (nm) WxDxH)800Packed Weight Gop)820External FinishPaccod doidDen Type of NaticNations SciellDor Type of NaticNations SciellDor Type of NaticNations SciellOper Doro PapthRepfacional MathematicOper Doro PapthVisAdjustable FordVisCalcus Adjustable FordVisOper Doro SciellVisOper Doro PapthVisAdjustable FordVisParthole SciellVisParthole SciellVisParthole SciellVisParthole SciellVisParthole SciellVisNumber Of Shelf PacificSocial SciellNumber Of Shelf PacificSocial SciellNumber Of Shelf PacificSocial SciellNumber Of Shelf PacificSocial SciellShelf MaterialVisNumber Of Shelf PacificSocial SciellShelf MaterialVisShelf MaterialVisNumber Of Shelf PacificSocial SciellShelf MerialSocial SciellShelf MerialSocial SciellShelf MerialSocial SciellShelf MerialSocial SciellShelf MerialSocial SciellShelf MerialSocial SciellShelf Merial		720
Picked Neight (mm)90Packed Neight (mm)200Packed Neight (mm)200Packed Neight (mm)000650530Packed Neight (kg)000650530Imman Dimensions(MOXDMA)000650530Enternal FinishPeocated staldDerof NeightPeocated staldInternal Dimensions(MOXDMA)Names StellDor TypeNames StellReplaceble Dor SealVis CompationOpen Dor SealVis CompationDeroto SealStell StellDorto StellName CompationNames CharlesName CompationPathole StellStol Stell StellDorto Stell StellStell Stell	Unit External Depth (mm)	800 (excl handle)
Picked Neight (mm)90Packed Neight (mm)200Packed Neight (mm)200Packed Neight (mm)000650530Packed Neight (kg)000650530Imman Dimensions(MOXDMA)000650530Enternal FinishPeocated staldDerof NeightPeocated staldInternal Dimensions(MOXDMA)Names StellDor TypeNames StellReplaceble Dor SealVis CompationOpen Dor SealVis CompationDeroto SealStell StellDorto StellName CompationNames CharlesName CompationPathole StellStol Stell StellDorto Stell StellStell Stell	Unit External Height (mm)	2040
Packed Weight Gap220Packed Weight Gap165Packed Weight Gap165Internal Dirension (mm) (VADAH)5006558/350Temperature Range42/10-104External FinishProcedid stealInternal TinishProcedid stealDor TypeRajft Hand HingidDor TypeRajft Hand HingidReplaceb Doro SeasoViaOpen Doro DesoroViaCokVia McCancelAdjustable FeetCalcis x4PortholeViaTemperature Diptay On PanelElo / TouchseenTemperature Diptay On PanelElo / TouchseenTemperature Diptay On PanelViaNumber Of Shell PocitionsSalos/SorminNumber Of Shell PocitionsSalos/SorminShell MarcinalVicceral viaNumber Of Shell PocitionsSalos/SorminShell MarcinalNoread viaShell MarcinalNoread viaShell MarcinalSind Carcel viaNumber Of Shell PocitionsSalos/SorminShell MarcinalNoread viaShell MarcinalNoread viaShell MarcinalNoread viaShell MarcinalNoread viaShell MarcinalNoread via		810
Packed Weight Gap220Packed Weight Gap165Packed Weight Gap165Internal Dirension (mm) (VADAH)5006558/350Temperature Range42/10-104External FinishProcedid stealInternal TinishProcedid stealDor TypeRajft Hand HingidDor TypeRajft Hand HingidReplaceb Doro SeasoViaOpen Doro DesoroViaCokVia McCancelAdjustable FeetCalcis x4PortholeViaTemperature Diptay On PanelElo / TouchseenTemperature Diptay On PanelElo / TouchseenTemperature Diptay On PanelViaNumber Of Shell PocitionsSalos/SorminNumber Of Shell PocitionsSalos/SorminShell MarcinalVicceral viaNumber Of Shell PocitionsSalos/SorminShell MarcinalNoread viaShell MarcinalNoread viaShell MarcinalSind Carcel viaNumber Of Shell PocitionsSalos/SorminShell MarcinalNoread viaShell MarcinalNoread viaShell MarcinalNoread viaShell MarcinalNoread viaShell MarcinalNoread via		
Packedwight (g)EditInternal Dimensions (mot) (WxDxH)600x/66x/630External FinishPre coated SkelExternal FinishPre coated SkelType of PlasticNADoor TypeRay Kand HingedDoor StyleGas / Stel CosingOpen Door DepthRay Kand HingedReplacable Door SeorKesAlgustatie FeedCastor (Stel Cosing)Open Door SeorKesAlgustatie FeedCastor (Stel Cosing)Open Door SeorKesAlgustatie FeedCastor (Stel Cosing)PortholeKesReplacable Door SeorKesRotholeCastor (Stel Cosing)Porthole SizeCastor (Stel Cosing)Porthole SizeCastor (Stel Cosing)Rothole SizeCastor (Stel Cosing)Rothole SizeStel Cosing)Rothole SizeStel Cosing)Number Of Shelf PositionsKesStel Size Cosing)KesNumber Of Shelf PositionsStel Size Cosing)Shelf SizeStel Size Cosing)Shelf Size Cosing)Castor (Stel Cosing)Shelf Size Cosing)Castor (Stel Cosing)Shelf Size Cosing)Castor (Stel Cosing)Shelf Size Cosing)Stel Size Cosing) <th></th> <th></th>		
Internal Dimensions (mm) (Wx0x04)6000 (KS005000)Temperature Range420 to 480External FinishPerconted stellInternal FinishSamikes StellDoor Type of PlatishMainDoor Type of PlatishMainReplacable Door SealVisOpen Door SealVisOpen Door SealVisAdjutable FeetCastors 4PortholeYesPorthole StallCastors 4Replacable Door SealYesPorthole YesSaminAdjutable FeetYesPorthole YesYesPorthole YesYesPorthole YesYesNumber Of Shelf PositionsYesNumber Of Shelf PositionsYesNumber Of Shelf PositionsYesNumber Of Shelf PositionsSalor GommShelf StaceSalor GommShelf MaterialNor ControllerNumber Of BasetsNorInterior UptYesSpark FreeNorSpark FreeNorSpark FreeNorSpark FreeNorNumber Of PostersYesSpark FreeNorPortonertypeYesNumber Of PostersNorSpark FreeNorPortonertypeYesNumber Of PostersYesPortonertypeYesNumeer Of Posters<		
Temperature Range42C to 48CExternal FinishPrecoded stellInternal FinishSanles StellType of PasticN/ADoor TypeRight Hard HingedDoor TypeGias / Sef ClosingOpen Door DepthHeSimReplacedale Door SalaYesOpen Door SensorYes / McChailedLockYes / McChailedAdjustable FeetCastons x4PortholeYesPorthole SelaSamTemperature Display On PanelLED / TouchscienenTemperature Display On PanelLED / TouchscienenTemperature AlarmYesNumber Of ShelvesSandorfformShelf NacionalYesAddible AlarmsYesVisual AlarmsYesShelf NacionalSondofformShelf NacionalOShelf NacionalOShelf StelSondofformShelf NacionalYesLight ArtistapeOLight ArtistapeOShelf StelSondofformShelf StelSondofform </th <th></th> <th>600x665x1530</th>		600x665x1530
ExtendiPrecode stellInternal FinishStarlies SteelInternal FinishStarlies SteelInternal FinishNADoor Type of PasticRight Hond HingedDoor StyleGoor Steel Sciel		
Type of PlasticN/ADor TypeRight Hand HingedDor StyleGlask Self ClosingOpen Dor Dor Dor Dor Dor Dor SonVesReplacable Door SealVesLockVesLockVesCastors x4Castors x4Adjustable FeetVesPortholeVesPorthole Size32mmTemperature Display On PanelVesAdubte AlarmsVesRemote Alarm ContactsVesNumber Of Shele SizeSocialNumber Of Shele SizeSocialShelf MaterialVes Casted wireNumber Of Shele SizeSocialShelf MaterialVes Casted wireNumber Of Shele SizeSocialShelf MaterialVes Casted wireShelf MaterialNoDard Size Size Size Size Size Size Size Size		Pre-coated steel
Dor TypeRght Hand HingadDor TypeGass / Sel CouragOpen Door DephMeSrmanReplaceable Door SealYesOpen Door SensorYesCackYes / MechancalAdjustable FeetCactors x4PortholeYesPorthole Size2mmTemperature Display On PanelLED / TouchscreenTemperature AlarmYesAudible AlarmsYesMumber Of Shelves5Number Of ShelvesS0x650mmShelf Size30x650mmShelf SizeS0x650mmShelf SizeS0x650mmShelf AlarmsVesLight AlarmsQoen Door ShelvesShelf SizeS0x650mmShelf SizeS0x650mm <th>Internal Finish</th> <th>Stainless Steel</th>	Internal Finish	Stainless Steel
Door TypeRight Hand HingedDoor TypeGlass / Self CoorgOpen Door DepthGlefminReplaceable Door SealYesOpen Door SensorYesLokYes/McchancalAdjustable FeetCastors x4PortholeYesPorthole Size2mmTemperature Display On PanelLED / TouchscreenTemperature AlarmYesMonto CostalYesAudible AarmsYesNumber Of Shelves5Number Of Shelves5Shelf Size30x650mmShelf Size50x650mmShelf Size50x650mmShelf Size50x650mmShelf MaterialVC Costed wireNumber Of Shelves0Number Of Shelves0Shelf ActivationVC Costed wireNumber Of Shelves0Shelf ActivationVC Costed wireNumber Of Shelves0Shelf ActivationVC Solet WireNumber Of Shelves0Shelf MaterialVoor Switch / ControllerShelf ActivationVoor Switch / ControllerShelf ActivationSign Sign Sign Sign Sign Sign Sign Sign	Type of Plastic	N/A
Door StyleGlass / Self ClosingOpen Dor Depth1455rmReplacaela Door SenorYesOpen Dor SenorYesLockYes / McchanialAdjustable FeelCastors x4PortholeYesPorthole SizeSamonTemperature Diptay On PanelLED / TouchscreenTemperature Diptay On PanelLED / TouchscreenAudite AlarmaYesAudite AlarmaYesNumber Of ShelvesSNumber Of ShelvesSStor Staff PositionsONumber Of ShelvesSOx60mmNumber Of ShelvesONumber Of Shelf PositionsONumber Of Shelf PositionsOShelf MarcingVesShelf MarcingNoShelf MarcingSox60mmShelf MarcingOShelf MarcingOShelf MarcingOShelf MarcingSox60mmShelf MarcingSox60mmShelf MarcingOShelf MarcingSox60mmShelf MarcingSox60mm		
Open Door Depth1466mmReplacable Door SealYesOpen Door SensorYesLockYes / MechanicalAdjustable FeetCastors s/aPortholeYesPorthole Size32mmTemperature Display On PanelLED / TouckscreenTemperature Display On PanelYesRemote AlarmYesNumber Of ShelvesYesNumber Of ShelvesSNumber Of ShelvesSShelf NachYesNumber Of ShelvesSShelf SizeS0x660mmShelf SizeS0x660mmNumber Of ShelpetSoShelf SizeS0x660mmShelf SizeS0x660mmShelf SizeS0x660mmShelf SizeS0x660mmShelf SizeS0x60mmShelf SizeS0x620mmShelf		
Repiaceable Door SensorYesOpen Door SensorYes/MechanicalLockYes/MechanicalAdjustable FeetCastors x4PortholeYesPorthole SizeZarmTemperature Display On PanelLED/TouchscreenTemperature Display On PanelLED/TouchscreenAddibe AlarmsYesRemote Alarm ContactsYesNumber Of ShelvesSoNumber Of ShelvesSoSheff PositionsSoNumber Of ShelvesSoSheff PositionsSoSheff NeticinsPVC contal wireItapir TypeLEDLight TypeSoSheff NeticinsSoSheff NeticinsSo </th <th></th> <th></th>		
Open Door SensorYesLockYes/MchanicalAdjustable FoetCastors x4Adjustable FoetCastors x4PortholeYesPorthole Size32mmTemperature Display On PanelUED/ TouchsreenTemperature Display On PanelYesAudible AlarmsYesRemote Alarm ContactsYesNumber Of Shelves5Number Of Shelves5Suff SizeS0x650mmNumber Of Shelves50x650mmShelf MaterialPVC coatel wireNumber Of Shelves0Shelf NaterialPVC coatel wireNumber Of Shelves0Shelf SizeS0x650mmShelf Size <td< th=""><th></th><th></th></td<>		
Adjustable FeetCastors x4PortholeYesPorthole SizeSammPorthole SizeSammPorthole SizeSammTemperature Display On PanelLED / TouchscreenTemperature Display On PanelLED / TouchscreenRemote Alarm ContactsYesAudible AlarmsYesVisual AlarnsYesNumber Of Shelves5Number Of ShelvesSolosSommShelf SizeSolosSommShelf SizeSolosSommShelf AterialVC coated wireNumber Of ShaketsOShelf AterialVesShelf SizeSolosSommShelf SizeSolosSomm <t< th=""><th></th><th></th></t<>		
Adjustable FeetCastors x4PortholeYesPorthole SizeSammPorthole SizeSammTemperature Display On PanelLED / TouchscreenTemperature Display On PanelLED / TouchscreenTemperature AlarmYesRemote Alarn ContactsYesAudible AlarnsYesNumber Of ShelvesSaNumber Of ShelvesSaShelf SizeSaloköommShelf SizeSaloköommInterior LightVic Coated wireInterior LightVesLight ArgVesLight ArgLight ArgShelf SizeSaloköommShelf SizeSaloköommSh	Lock	Yes / Mechanical
Porthole Size32mmTemperature Display On PanelLED / TouchscreenTemperature AlarmVesRemote Alarm ContactsVesAudible AlarmsVesAudible AlarmsVesNumber Of Shelves5Number Of Shelves20Sheff Size30x650mmSheff Size30x650mmIterior LightVesIterior LightVesLight TypeLEDLight Attraiton0Spark FeeNoDer Switch / ControllerNoBattery BackyNoController TypeUseBattery BackyVersesController TypeOperational ControllerBattery BackyVersesController TypeSpark FreeAnnber Of Photes2Rattery BackyVersesController TypeMerical Sind DownloadNumber Of Photes2Refregent TypeVerses / SD DownloadNumber Of Photes2Prober TypeColocal Controller ConnectivityNumber Of Photes2Prober TypeMic Controller ConnectivityNumber Of Photes2Prober TypeColocal ConnectivityNumber Of Photes2Prober TypeColocal ConnectivityNumber Of Photes2Prober TypeColocal ConnectivityNumber Of Photes2Prober Type20/202/VRefregent Type20/202/VProber Type20/202/VProber Type20	Adjustable Feet	
Temperature Display On PanelLED / TouchscreenTemperature AlarmYesRemote Alarm ContactsYesAudible AlarmsYesAudible AlarmsYesNumber Of Shelves5Number Of Shelf Positions20Shelf MaterialPVC coated wireNumber Of Baskets0Number Of Baskets0Number Of Shelf Positions0Number Of Shelf Positions0Number Of Baskets0Number Of Baskets0Spark FreeNoSpark FreeNoDefrost SettingNoController TypeDigital / WirelessBattery Back UpYesController ConnectivityYireless / SD DownloadNumber Of Probes2Probe TypeNoAnbient Temperature Range10-32CRefrigerant TypeKVoltage SupplySO2v40VFrequency (Hz)SO2v40VInsulation ThicknessSom	Porthole	Yes
Temperature AlarmYesRemote Alarm ContactsYesAudible AlarmsYesAudible AlarmsYesNumber Of Shelves5Number Of Shelves5Sheff Staie530x650mmSheff AtarialPVC coated wireNumber Of Baskets0Interior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanVesSpark FreeNoDefrost SettingAutoController TypeDigital / WrelessBattery Back UpYesController Type10 200Ambient Of Probes2Probe Type10 32CRefigerant TypeUKVoltage Supply0042Sing Supply20040V/Frequency (Hz)SingSupplation ThicknessSingSupplation ThicknessSing	Porthole Size	32mm
Remote Alarm ContactsYesAudible AlarmsYesVisual AlarmsYesNumber Of Shelf Positions5Shumber Of Shelf Positions20Shelf MaterialPVC coated wireNumber Of Baskets0Interior LightYesLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeJigli / WirelessBattery BackUpYesController OrnectivityWireless/SDD AlanceNumber Of Pobes2Probe TypeAl/ LoadAndient Temperature RangeIo 32CRefrigerant TypeKesPlags Light TypeUKVoltage SupplyKesSpark FreeDoor Sutch / ControllerFanYesController ConnectivityMirelessBattery BackUp2Controller ConnectivityMireless/SDD ControllerAmbient Temperature RangeIo 32CRefrigerant TypeZo-240VFrequency (Hz)SOHZInsulation ThicknessSam	Temperature Display On Panel	LED / Touchscreen
Audible AlarmsYesVisual AlarmsYesNumber Of Shelves5Number Of Shelves20Shelf Size30x650mmShelf Size53x650mmShelf MaterialPVC coated wireNumber Of Baskets0Interior LightYesLight TypeEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoOntroller TypeDigital / WrelessBattery Back UpYesController TypeDigital / WrelessBattery Back UpXir Coated MinedProbe TypeArl LoadAmbient Gregnerature RangeNor 3QCRefrigerant TypeUKVoltage SupplyYesFrequency (Hz)SQCSpark SupplySQCStation ThicknessSQCSupplySQCSupplySQCSupplySoltz </th <th>Temperature Alarm</th> <th>Yes</th>	Temperature Alarm	Yes
Visual AlarmsYesNumber Of Shelves5Number Of Shelf Positions20Shelf SizeS30x650mmShelf MaterialS30x650mmNumber Of Baskets0Interior LightYesLight TypeLEDLight TypeDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WrelessBattery Back UpVesController Probes2Probe TypeAir / LoadAmbient Temperature RangeNoAmbient TypeUkVoltage SupplyXeyOvAlFrequency (Hz)SOv240VInsulation ThicknessSolfSupplation ThicknessSolfSupplation ThicknessSolf	Remote Alarm Contacts	Yes
Number Of Shelves5Number Of Shelf Positions20Shelf Size530x650mmShelf Size530x650mmShelf Size500x650mmShelf Size0Number Of Baskets0Interior LightVesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefros SettingAutoController TypeDigital / WrelessBattery Back UpVesController ConnectivityWreless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature RangeNo.32CRefrigerant TypeLipVoltage Supply20>2v40vFrequency (Hz)SoHzInsulation ThicknessSmm	Audible Alarms	Yes
Number Of Shelf Positions20Shelf SizeS30x650mmShelf MaterialPVC coated wireNumber Of Baskets0Interior LightYesLight ActivationDoor Switch / ControllerEgatNoSpark FreeNoDefot StettingAutoController TypeDigital / WrelessBattery Back UpYesController ConnectivityWreless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefigerant TypeUKVoltage Supply20-240VFrequency (Hz)SommInsulation ThicknessSamm	Visual Alarms	Yes
Shelf Size530x650mmShelf MaterialPVC coated wireNumber Of Baskets0Interior LightVesLight TypeLEDLight ActivationDoor Switch / ControllerSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpVerOntroller ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeMireless / SD DownloadAmbient Temperature RangeNo.2Refrigerant TypeResoPlug TypeUKVoltage SupplySolor Suitol / Controller ConnectivityNumber Of Probes2Product TypeDigital / Wireless / SD DownloadAmbient Temperature RangeNo.2Refrigerant TypeSolor Suitol / Controller ConnectivityNumber Of Probes2Plug TypeUKStatistication SupplySolor SupplyStatistication SupplySolor SupplyStatistication SupplySolor SupplyInsulation ThicknessSomm	Number Of Shelves	5
Shelf MaterialPVC coated wireNumber Of Baskets0Interior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDgital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature RangeNoPlug TypeUKVoltage Supply20:240VFrequency (Hz)Smm	Number Of Shelf Positions	20
Number Of BasketsOInterior LightYesLight YpeDoor Switch / ControllerLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigtal / WrelessBattery Back UpYesController ConnectivityVerless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10-32CRefrigerant TypeUKVoltage Supply20-240VFrequency (Hz)SoHzInsulation ThicknessSamm	Shelf Size	530x650mm
Interior LightYesLight YpeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature RangeNo 32CPlug TypeUKVoltage SupplySO-2040VFrequency (Hz)SO-2040VInsulation ThicknessS8mm	Shelf Material	PVC coated wire
Light TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeKeVoltage Supply20-240VFrequency (Hz)SoHzInsulation ThicknessSamm	Number Of Baskets	0
Light ActivationDoor Switch / ControllerFanSpark FreeSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature RangeR290Plug TypeUKVoltage SupplySOHzFrequency (Hz)SoHzInsulation ThicknessSamm	Interior Light	Yes
FanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10.32CRefrigerant TypeUKVoltage Supply20.240VFrequency (Hz)SoftzInsulation ThicknessSomm	Light Type	LED
Spark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpViseless / SD DownloadController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature RangeNoRefrigerant TypeUKVoltage SupplyLocadFrequency (Hz)SO/2020Insulation ThicknessSomm	Light Activation	Door Switch / Controller
Defrost SettingAutoController TypeDigital / WirelessBattery Back UpVisController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR29OPlug TypeUKVoltage Supply200-240VFrequency (Hz)SOHzInsulation ThicknessS8mm	Fan	Yes
Controller TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR29OPlug TypeUKVoltage Supply20-240VFrequency (Hz)SOHzInsulation ThicknessS8mm	Spark Free	No
Battery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range0 - 32CRefrigerant TypeKePlug TypeUKVoltage Supply202-40VFrequency (Hz)SolHzInsulation ThicknessSemme	Defrost Setting	Auto
Controller ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 · 32CRefrigerant TypeR290Plug TypeUKVoltage Supply220·240VFrequency (Hz)SOHzInsulation ThicknessS8mm	Controller Type	Digital / Wireless
Number Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR29OPlug TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness58mm	Battery Back Up	Yes
Probe Type Air / Load Ambient Temperature Range 10 - 32C Refrigerant Type R290 Plug Type UK Voltage Supply 220-240V Frequency (Hz) 50Hz Insulation Thickness 58mm	Controller Connectivity	Wireless / SD Download
Ambient Temperature Range 10-32C Refrigerant Type R290 Plug Type UK Voltage Supply 200-240V Frequency (Hz) 50Hz Insulation Thickness 58mm	Number Of Probes	2
Refrigerant Type R290 Plug Type UK Voltage Supply 220-240V Frequency (Hz) 50Hz Insulation Thickness 58mm	Probe Type	Air / Load
Plug Type UK Voltage Supply 220-240V Frequency (Hz) 50Hz Insulation Thickness 58mm	Ambient Temperature Range	10 - 32C
Voltage Supply 220-240V Frequency (Hz) 50Hz Insulation Thickness 58mm	Refrigerant Type	R290
Frequency (Hz) 50Hz Insulation Thickness 58mm	Plug Type	UK
Insulation Thickness 58mm	Voltage Supply	220-240V
	Frequency (Hz)	50Hz
Anti Microbial Handle Yes / BioCote	Insulation Thickness	58mm
	Anti Microbial Handle	Yes / BioCote





Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.