

Three-Dimensional Shaker TL 10



Description

The Three-Dimensional Shaker TL 10 works with slow, three-dimensional motion. The angle of tilt is adjustable between 0° and 9° and the shaking speed between 1 and max. 23 rpm. The shaking platform of 340 x 340 mm can be loaded with max. 10 kg.

Basic Equipment

Basic device incl. basic tray and rubber mat

Details

Motion:	three-dimensional orbital motion
Shaking platform:	340 x 340 mm
Max. load:	10 kg
Shaking speed:	1 - 23 rpm, steplessly adjustable

Angle of tilt: 0° to 9° einstellbar
Timer: 0 - 120 min / continuous
Order No.: 6117 000
Accessory: Multi-storey rack system WS / TL

Technical specifications

Electrical supply: 230 V or 115 V, 50 / 60 Hz please indicate in case of order
Enclosure protection: IP 21
Heat emission: approx 7 - 10 W
Ambient temperature:: 5°C to 50°C
Relative humidity: ~ 85 %
Dimensions (w x d x h): 355 x 450 x 205 mm
Weight: 18,5 kg



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

