

Three-Dimensional Shaker TL 2



Description

The Laboratory Shaker TL 2 works with slow, three-dimensional motion for gentle, uniform wetting. Well suited for petri dishes, culture bottles etc.

Basic Equipment

Basic device incl. basic tray and rubber mat

Details

Motion: three-dimensional orbital motion
Shaking platform: 220 x 220 mm
Max. load: 2 kg

Shaking speed: 1 - 22 rpm, steplessly adjustable
Angle of tilt: 8° fixed
runtime: 0 - 9 h 59 min / continuous
Order No.: 6139 000
Accessory: Additional Tray TL 2

Technical specifications

Electrical supply: 100 - 240 V, 50 / 60 Hz
Enclosure protection: IP 21
Heat emission: max. 3 W
Ambient temperature:: 5°C to 45°C
Relative humidity: ~ 85 %
Dimensions (w x d x h): 250 x 415 x 118 mm
Weight: 9,1 kg



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

