

Powdermax®



Esco Powdermax 1 Powder Weighing Balance Enclosure
Model PW1-3A_

Powder Weighing Balance Enclosure

Laboratory operations involving weighing, mixing and dispensing hazardous or nuisance powders can now be performed safely and economically with the Esco Powdermax 1 Powder Weighing Balance Enclosure. The enclosure's unique design maintains balance stability to 4 decimal places without compromising containment.

Designed specifically for powder containment applications, the Powdermax Enclosure employs carefully directed inward airflow at the face of the enclosure to protect the operator from exposure to hazardous powders or potent pharmaceutical compounds. The aerodynamically designed enclosure reduces airflow turbulence for maximum containment while minimizing the effect that air drafts may have on sensitive weighing balances. The enclosure design exceeds the containment requirements of ANSI/ASHRAE 110 as proven by independent type testing. All exhaust air is HEPA-filtered, removing virtually all particulate matter, before recirculation to the laboratory.

Designed for Enhanced Usability and Efficiency

The Powdermax 1 is designed specifically to provide the operator with a high level of usability, comfort and visibility.

- A 13-degree sloped front allows easy access to the work zone, eliminating operator fatigue and increasing productivity.
- Transparent 6 mm (0.2") frameless acrylic front and sides enhance visibility and operator comfort during longer periods of operation. The self-supporting pre-tensioned hinges on the front window provide easy access during loading and start-up.
- Ergonomically designed apertures for hands simultaneously provide maximum movement within the work zone while protecting the operator. The curved front edge minimizes airflow turbulence and improves user comfort.

- Electronic ballast for the fluorescent lighting provides zero-flicker with increased energy efficiency, reliability and service life with a lower heat output.
- Two electrical pass throughs on the back wall of the unit provide convenient access to power sources for equipment.
- The spacious interior dimensions will easily accommodate large analytical balances.


Enhanced Filtration System

The enclosure's unique filtration system ensures the highest level of protection for the operator.

- The Powdermax 1 provides enhanced safety to laboratory personnel by drawing air across the front opening in the hood at a controlled rate, preventing the escape of powders and particulate matters into the general laboratory environment.
- A unique filter mounting system eliminates bypass leaks inherent in conventional clamping systems.
- The Powdermax 1 is equipped with a generously sized HEPA filter system, rated at >99.99% efficiency for 0.3 micron sized particles.
- The aerodynamically designed system constructed of 1.2 mm (16 gauge) epoxy powder-coated electrogalvanized steel delivers maximum containment by ensuring airflow uniformity throughout the work chamber of the cabinet.
- Since HEPA-filtered air is recirculated to the laboratory, the enclosure does not have to be connected to an extraction/exhaust system, resulting in low operating costs and mobility.

User-Friendly Control System

The user-friendly Esco Sentinel™ micro-processor based control system is fully configurable according to operator's requirements and comes equipped with a number of enhanced features to



Powdermax 1 Powder Weighing Balance Enclosure Airflow

Blower
Exhaust HEPA Filter

- HEPA-filtered air
- Unfiltered / potentially contaminated air
- Inflow air

- Room air is drawn in across the front of the cabinet with an average velocity of 0.5 m/s (100 fpm).
- Air is drawn up through the cabinet's work zone and forced through the HEPA filter (>99.99% typical efficiency for 0.3 micron sized particles).
- The state-of-the-art baffle system ensures airflow uniformity throughout the cabinet's main chamber.
- The HEPA filtered air then returns to the laboratory stripped of all airborne contaminants or is vented through the optional exhaust collar to exhaust ducting for enhanced safety.

promote cabinet usability.

- Accurate true airflow velocity sensing technology measures all critical cabinet airflow parameters allowing superior monitoring. Temperature compensated sensors ensure increased accuracy.
- Password-protected administration can be set to restrict access to the main menu.
- Solid state variable speed controllers offer superior control over conventional "step" controllers. The built in RFI and noise filters eliminate interference with adjacent instrumentation.
- A bright, easy-to-read, LCD display provides continuous monitoring of cabinet airflow.
- Audible and visual alarms ensure operator and environmental protection by alerting the user in the event of low airflow or unsafe sash positions.
- When the cabinet is switched on, its automatic warm-up cycle is activated, purging all contaminants from the work zone prior to use.
- An automatic post-purge cycle can be configured on shutdown, purging all residual contaminants before deactivation.

Highest Quality Enclosure Construction

All Esco cabinets are constructed to the highest quality using the finest materials.

- The enclosure's head unit is constructed of electrogalvanized steel with abrasion-resistant powder-coated finish.
- External surfaces are coated with Esco Isocide™ antimicrobial coating to protect against surface contamination and inhibit bacterial growth. Isocide eliminates 99.9% of surface bacteria within 24 hours of exposure.
- The enclosure is supplied with a chemical and abrasion resistant phenolic resin removable work surface. The solid work surface minimizes transmission of fan vibration to the user's weighing balance.

Blower Efficiency

The Powdermax 1 incorporates an energy efficient external rotor motor design which reduces operating costs and has extremely low noise and vibration levels. The cabinet blower system creates an inflow of air from the ambient environment into the cabinet with an average velocity of 0.4 m/s (80 fpm).

Designed and Built to Exceed Safety Criteria

All components used in Esco products meet or exceed all the applicable safety requirements and are UL listed/recognized. The Powdermax 1 is compliant with International Standards. The cabinet is designed to meet the general safety requirements of EN 61010-1, EN 61326 Class B.

Options and Accessories

The Powdermax 1 is available with a number of options and accessories to meet your needs. These include:

- Mobile cart with foldable trays
- Height-adjustable lab chair
- Ergonomic foot rest

Further customization specifications are available upon request.

Warranty

The Powdermax 1 is warranted for 3 years excluding consumable parts and accessories. Contact your local sales representative for specific warranty details.

PW1 Microbalance Stability Testing

Weighing Accuracy Test on Esco Powdermax™ Powder Weighing Balance Enclosure



The Esco PowderMax™ cabinet at nominal airflow can provide a stable work condition for sensitive powder weighing work with extremely low standard deviation in the range of 0.000001 to 0.000011 for weighing 20g, 5g, and even 0.5g objects.

PW1 Surrogate Powder Testing

Active Pharmaceutical Ingredients (API) Surrogate Containment Testing on Esco Powdermax™ Powder Weighing Balance Enclosure



The Esco PowderMax™ Powder Weighing Balance Enclosure, operating at 0.50 m/s (100fpm) average inflow, was demonstrated to contain surrogate API (naproxen sodium), at an OEL of 26.3 microgram/m³, for a challenge of repetitive weighing of 20 x 1-gram quantities of API, independent of the operator's level of skill.

Powdermax®

Containment / Pharma Products • Powder Weighing Balance Enclosures

General Specifications, Powder Weighing Balance Enclosure, Model PW1-3A_


**Note to Customer: Insert electrical voltage number into last number digits _ when ordering.*

| | | |
|--|--|--|
| Nominal Size | 0.9 meters (3 ft) | |
| External Dimensions (W x D x H) | 840 x 700 x 1125 mm (33.0" x 27.6" x 44.3") | |
| Internal Work Area, Dimensions (W x D x H) | 820 x 650 x 848 mm (32.3" x 25.6" x 33.5") | |
| Usable Work Zone | 0.52 m ² (5.6 sq.ft) | |
| Air Volume (at Initial Velocity) | 234 m ³ /h (138 cfm) | |
| Inflow Velocity | Initial setpoint: average of 0.5 m/s (100 fpm) measured in plane of work aperture | |
| HEPA Filter Efficiency | >99.99% at 0.3 microns | |
| Sound Emission per NSF / ANSI 49 | <55 dBA at initial blower speed setting measured at typical operator work position | |
| Fluorescent Lamp Intensity at Zero Ambient | >560 Lux (> 52 foot-candles) | |
| Cabinet Construction | Main Body | 1.2 mm / 0.06" / 16 gauge electro-galvanised steel with white oven-baked epoxy-polyester powder-coated finish. |
| | Work Zone | 6 mm (0.2") Acrylic |
| | Side Walls | 6 mm (0.2") Acrylic |
| Power Rating | 225W (230V, AC units) 270W (115V, AC units) | |
| Net Weight ** | 66 kg (145.5 lbs) | |
| Shipping Weight ** | 96.4 kg (212.5 lbs) | |
| Shipping Dimensions, Maximum (W x D x H)** | 1000 x 1100 x 1180 mm (39.8" x 43.3" x 46.5") | |
| Shipping Volume, Maximum** | 1.3 m ³ (45.9 cu.ft.) | |
| Electrical* | Model | Voltage |
| | PW1-3A1 | 220-240V, AC, 50Hz, 1Ø |
| | PW1-3A2 | 110-120V, AC, 60Hz, 1Ø |
| | PW1-3A3 | 220-240V, AC, 60Hz, 1Ø |

* Additional voltages may be available; contact Esco for ordering information.
** Cabinet only; excludes optional stand.

3

Powdermax 1 Powder Weighing Balance Enclosure Technical Specifications



| | | |
|-----------------------------|---------------------------|--|
| Standards Compliance | Containment | Electrical Safety |
| | ANSI/ASHRAE 110-1995, USA | UL-61010-1, USA CAN/CSA-C22-2 No.61010-1 EN-61010-1, Europe IEC61010-1, Worldwide |



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.