



UV Cleaner-Recirculator

UV cleaner-recirculators

UVR-M UV cleaner-recirculator general purpose, one lamp

UVR-Mi UV cleaner-recirculator advanced, two lamps

UVR-M

UV cleaner-recirculator

Easy to use UV cleaner-recirculator ideal for air disinfection in research laboratories and clinics. UV air flow cleaner-recirculator consists of one germicidal UV lamp, a fan unit equipped with dust filters and a control unit confined in a flow through chamber.

Full user protection from direct UV radiation

Simple to operate

Convenient fixation on walls or mount on a movable tripod (optional)



Applications

- Kindergartens, research laboratories, veterinary clinics, schools and offices.

UVR-Mi

UV cleaner-recirculator

Powerful and efficient UV cleaner-recirculator with two UV lamps providing air disinfection in research laboratories and clinics. UV air flow cleaner-recirculator consists of two germicidal UV lamps, a fan unit equipped with dust filters and a control unit confined in a flow through chamber.

Full user protection from direct UV radiation

Two operation modes - short time (under timer control) and continuous operation

Simple to operate

Convenient fixation on walls or mount on a movable tripod (optional)



Two UV lamps for more powerful UV air disinfection.

Easy to read LCD screen for better control over the device performance.

UV lamp lifetime counter indicates number of working hours left in the lamp.

Convenient fixation on walls. Optional mounting on a movable tripod for easy transportation.

Quiet operation (33-37dBa) and low energy consumption (150W).

Extremely quiet in operation - fits unobtrusively in the workplace.

Integral digital timer - 1 min to 24 hours or non stop operation.

Automatic ON/OFF switch - no need to turn the device on and off.

Lamp fault detection indicates UV lamp failure.

2 year warranty



Made in Europe

Applications

- Kindergartens, research laboratories, veterinary clinics, schools and offices.


UV cleaner-recirculators

Technical specifications

			
		UVR-M	UVR-Mi
		UV cleaner-recirculators	
Dimensions	w x d x h mm	110 x 135 x 660	110 x 135 x 660
UV radiation source	25W Bactericidal, TUV25WG13 UV-C	1 lamp	2 lamps
UV air flow productivity	m3/hour	14	
UV radiation level		18 mW / cm2 / sec	36 mW / cm2 / s
Full user protection from direct UV light		•	•
Display		-	LCD
Timer		-	1 min-24 hrs / non-stop
Wall bracket			•
UV lamp operation indicator			•
UV lamp lifetime counter		-	•
Automatic ON/OFF switch		-	•
Lamp fault detection		-	•
Power consumption	230V	125VA (540mA)	110W (0.5A)
	120V	160 VA (1.3A)	110W (0.5A)
Nominal operating voltage		230V (50 Hz) or 120V (60 Hz)	230 V (50 Hz)
Weight	kg	3.4	3.4

UV cleaner-recirculators

Options and accessories

		UVR-M	UVR-Mi
UVR-S			•

w.
t.
e.

►
t
in



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.