

Haier Biomedical

Intelligent Protection of Life Science

Typical Performance Characteristics in 25°C Ambient







Specifications

			DW-861	L829		
	Cabinet Type		Upright	- - - - - Functions -	High/Low Temperature	Y
	Climate Class		N		Hot Condenser	Y
Technical	Cooling Type		Direct cooling		Power Failure	Y
Data	Defrost Mode		Manual		High/Low Voltage	Y
	Refrigerant		HC		Sensor Frror	Y
	Sound Level (dB (A))		52			-
Performance Control	Cooling Performance (°C)		-86		Low Battery	Y
	Temperature Range (°C)		-40~-86		High Ambient Temperature	Y
	Controller		Microprocessor		Door Ajar	Y
	Display		LCD		Caster	Y
Electrical Data	Power Supply (V/Hz)		220~240/50		Foot	Y
	Power (W)		1700	_	Porthole	Y/2
	Electrical Current (A)		10	_	Shelves/Inner Doors	
Dimensions	Capacity (L/Cu.Ft)		829/29.3	_		3/4
	Net/Gross Weight (approx)	kg	380/410		USB Interface	Y
		lbs	837.7/903.9	Accessories	Remote Alarm	Y
	Interior Dimension (W*D*H)	mm	870*716*1310	_	5V Power Supply Port	Y
		in	34.3*28.2*51.6	_	Temperature Chart Recorder	Optional
	Exterior Dimension (W*D*H)	mm	1153*980*1980	_	RS485 Port	Standard
		in	45.4*38.6*78.0	_	CO2 Backup System	Optional
	Packing Dimension (W*D*H)	mm	1190*1045*2150		1 3	· ·
	- acting Dirich Sion (VV D 11)	in	46.9*41.1*84.6		LN2 Backup System	Optional
	Container Load (20'/40'/40'H)		10/20/20	Other	Certification	CE



ULT Freezer

DW-86L829

Making Your Lab More Intelligent and Reliable

Intelligent Inventory Management

10-inch touchscreen with single version inventory management allows users to easily record item locations, entry and exit records for intelligent stock management.

Safe and Reliable Storage

Temperature uniformity ≤±5°C, equipped with an intelligent temperature monitoring system, real-time temperature data monitoring function and multiple safety alarm system.

Energy Saving and Environmentally Friendly

The optimized hydrocarbon refrigeration system is more environmentally friendly and uses significantly less energy than older technologies, saving up to 30% on electricity. **ENERGY STAR certified.**

Haier













Ergonomic Design



Narrow Door Design

The freezer can pass through a 880mm wide door when the freezer door is open.



New Handle Design

Adopting exclusive slide design, easy to open and close the door



Pressure Equalization Port

Equipped with pressure equalization port for easy opening



•

Porthole

Two portholes as standard, allows for independent testing of cabinet temperature



ilter Design

Tool-free removable filter, making it easy and quick to clean the filter



Detachable Inner Door Design

Tool-free detachable inner door, ensuring easy and quick defrost



Product Advantages

Large Intelligent LCD Screen Visual Management

10-inch high-performance LCD capacitive screen, sensitive touch operation; intuitive display of inside temperature, ambient temperature, input voltage and other data and temperature curves.



Stored Items(materials) Management System

An accurate stored items management system was developed for users who don't use freezer racks, boxes and vials, the system easily records the items locations, entry and exit records and largely facilitate item inventory and statistics.



Single version (standard)



Professional version (optional)

The stored item management system was developed for users who use freezer racks, boxes and vials, the system can easily record the item locations, entry and exit records, facilitate item inventory and statistics with multi-screen interaction and reduce errors through secondary verification.

Equipped with Multiple Interfaces

Standard USB interface, capable of storing data for 10 years Standard remote alarm terminal and RS485 port







Multiple Options for Safe Management and Control Systems

Password lock as standard with optional fingerprint module, face recognition and punch card system. Multi-person management control option to ensure safe and secure storage.

Optional IoT System Real-time Monitoring


The IoT APP can monitor the operating status of the equipment anytime and anywhere. The unit is equipped with self-diagnose system faults and alarm functions, ensuring sample safety.



Safe and Secure with Multiple Alarms

Designed and manufactured with multiple alarm functions, such as high temperature alarm, low temperature alarm, sensor failure alarm, power failure alarm, low battery alarm, door ajar alarm and high ambient temperature alarm to name a few.





Precise Temperature Control ensures Safe Storage

The setting temperature is adjustable between -40 \sim -86°C, monitoring temperature curves in real time, and the temperature safety alarm system is the latest design and state-of-the-art technology.



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.