

Titramax 100



The compact model

- Titramax 100 is a compact and space-saving unit that accepts load capacities of 2 kg and space for four microtiter plates
- The 1.5-mm vibration orbit performs gentle mixing with best results using small sample volumes
- Set and continuously adjust the variable speed on the analog control knob from 150 to 1,350 rpm
- An analog process timer allows for unattended operation and can be set from 1 to 120 minutes. When the set time has elapsed an acoustic alarm will sound and the operation stops

Titramax 100 - Technical Data

| | |
|--------------------------------|--|
| Overheat protection | self-resetting |
| Permissible ambient conditions | 5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity |
| Weight | 5.5 kg |
| Protection class DIN EN 60529 | IP 30 |
| Timer | 1 |
| Rotation speed range | 150 - 1,350 rpm |
| Power input | 31 W |
| Dimensions (w/d/h) | 245 x 310 x 125 mm |
| Max. Load | 2 kg |
| Operating Mode | timer or continuous |
| Rotation speed setting | electronic control |
| Orbit / Stroke | 1.5 mm |
| Platform size | 220 x 220 mm |
| Accessories included | space for 4 microtiter plates |
| Angle | - |
| Motion | vibrating |



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.