

Reax 2 inc. universal adaptor



- Quickly clamps in 2 vessels of any size and accepts load capacities up to 1 kg
- Speed continuously adjustable from 20 to 100 rpm
- Universal adaptor allows for the use of various vessels of 50 - 160-mm height
- In addition, an optional adaptor is available for the use of 20 test tubes at a time

Reax 2 incl. universal adaptor - Technical Data

Overheat protection	self-resetting
Permissible ambient conditions	5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity
Weight	5.2 kg
Protection class DIN EN 60529	IP 21
Timer	-
Rotation speed range	20 - 100 rpm
Power input	27 W
Dimensions (w/d/h)	510 x 235 x 180 mm
Max. Load	1 kg
Operating Mode	-
Rotation speed setting	analog
Orbit / Stroke	-
Platform size	-
Accessories included	-
Angle	-
Motion	overhead



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.