



designed for scientists



IKA MultiDrive control

/// Data Sheet

Regardless of whether samples are hard, soft or fibrous – the IKA MultiDrive crusher can perform a wide range of crushing tasks involving coarse and fine crushing, thanks to the variety of vessels available. MultiDrive control mixes, grinds and is also fitted with a dispersion vessel and a disposable tube. There is a USB interface available for easy actuation and documentation respectively.

High performance

Excellent crushing performance is guaranteed by a combination of variable rotational speeds, ranging from 3000 rpm to 20 000 rpm,



designed for scientists

and a 1000 Watt output.

Interval operation

The option of interval programming is simple to activate at the press of a button. Interval operation is an asset during the coarse crushing of hard samples or for extra thorough blending.

Integrated cooling

A cooling system is integrated in the milling cup, which allows indirect heat dissipation. Thus, coolant and sample remain separate.

TFT-display

A clear TFT-display guarantees user-friendly operation.

Temperature measurement

MultiDrive control offers temperature measurement and vessel recognition using RFID. A temperature limit can be set for temperature-sensitive materials, or for specific planned reactions to protect against overheating.

Weighing function

The weighing function is also integrated into the user-friendly workflow of the IKA MultiDrive control. Weighing is performed before crushing using the same mixing cup, so that no transfer of contents is required.

Variety of vessels (accessory)

MultiDrive provides the right vessel for each grinding task. Vessels don't belong to the scope of delivery.



designed for scientists

Technical Data

Process type	batch
Operating principle	cutting/impact/blending/dispersing
Motor rating input [W]	1000
Motor rating output [W]	800
Speed range [rpm]	3000 - 20000
Speed deviation [%]	±5
Power-ON time [min]	5
Power-OFF time [min]	10
Motor principle	Brushless DC
Display	TFT
RFID reader/writer unit	yes
Temperature display	yes
Temperature measurement resolution [K]	0.1
Accuracy of temperature measurement [K]	±1
Temperature limit min. [°C]	-50
Temperature limit max. [°C]	120
Monitoring maintain time	yes
Weighing function	yes
Weighing range [g]	5 - 4000
Weighing resolution [g]	1
Load capacity weighing function max. [kg]	4
Weighing accuracy	±(0.3%+2) g
Vessels detection	yes
Ramp programming	yes
Dimensions (W x H x D) [mm]	300 x 350 x 250
Weight [kg]	8.5
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 31
USB interface	yes
Bluetooth interface	yes
Voltage [V]	220 - 240
Frequency [Hz]	50/60
Power input [W]	1000



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

