



Tube Mill 100 control

/// Data Sheet

The world's first patented Tube Mill 100 control is a batch mill with disposable grinding chambers. Eliminates possibility of cross-contamination and the effort of cleaning.

The Tube Mill 100 control accommodates larger grinding chambers with a maximum volume of 100 ml (MT 100).

The grinding chamber and cover are made of a transparent material so grinding tests can be observed at any time. The mill can be used for hard (Mohs hardness up to 5), dry and brittle materials. It is especially suitable for grinding seeds, such as corn and wheat.

The mill will only start when the hood is closed, making it safe to use.



- Clear and multilingual OLED display (incl. error code display)
- Timer, adjustable from 5s 3 min
- USB interface (control and document all parameters)
- Interval operation optional
- Infinitely variable speed (5,000 25,000 rpm)
- Various operating modes
- Adjustable safety speed and time
- Programmable and storable test conditions
- Reproducible test results
- Touch keypad
- Scope of delivery includes grinding chambers: 1 x MT 40; 1 x MT 100 and 1 x MMT 40



Technical Data

Process type	batch	
Operating principle	cutting/impact	
Motor rating input [W]	100	
Motor rating output [W]	80	
Speed range [rpm]	5000 - 25000	
Speed deviation [%]	±2	
Circumferential speed max. [m/s]	65	
Useable volume max. [ml]	100	
Feed hardness max. [Mohs]	5	
Feed grain size max. [mm]	10	
Power-ON time [min]	3	
Mill feed can be cooled in milling chamber with dry ice	yes	
Dimensions (W x H x D) [mm]	180 x 212 x 300	
Weight [kg]	2.8	
Permissible ambient temperature [°C]	5 - 40	
Permissible relative humidity [%]	80	
Protection class according to DIN EN 60529	IP 30	
USB interface	yes	
Voltage [V]	220 - 240	
Frequency [Hz]	50/60	
Power input [W]	100	



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





