



designed for scientists



ROCKER 2D digital

/// Data Sheet

Digital rocking shaker with adjustable speed for smooth mixing tasks. Used for homogeneous mixing in flasks, culture flasks, Petri dishes and tubes. Even with load and voltage fluctuations, shaking speed remains constant. An adjustable tilt angle ensures optimum adaption to the particular experimental conditions.

- Timer: Countdown, adjustable from 1 s to 99h 59min
- Counter: Display of shaking time
- Error Code Display
- Different attachments enable use for a variety of applications



IKAworlwide



IKAworlwide /// #lookattheblue



@IKAworlwide



designed for scientists

- Usable at 4 to 50 °C in incubators
- Easy operation with touch keypad
- Anti-slip rubber mat included
- Suitable for continuous operation
- Shaking diameter: 0 - 15° (angle)
- Speed range: 5 - 80 rpm



IKAworldwide



IKAworldwide /// #lookattheblue



@IKAworldwide



designed for scientists

Technical Data

Type of movement	rocking
Permissible shaking weight (incl. attachment) [kg]	2
Permissible ON time [%]	100
Speed min (adjustable) [rpm]	5
Speed range [rpm]	0 - 80
Speed display	7 segment LED
Speed control	1 RPM steps
Timer	yes
Timer display	7 segment LED
Time setting min. [s]	1
Time setting max. [min]	5999
Operating mode	timer and continuous operation
Rocking angle adjustable [°]	2.5 - 15
Shaking platform stackable	yes
Altitude (when shaking platform stacked) [mm]	30
Dimensions (W x H x D) [mm]	280 x 150 x 330
Weight [kg]	2.2
Permissible ambient temperature [°C]	4 - 50
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 21
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	24
DC Voltage [V=]	24
Current consumption [mA]	1000





Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

