



ICC 100 lite eco 8

/// Data Sheet

The compact immersion circulators of the lite series are powerful and of high quality, with a focus on essential basic functions, excellent performance and efficient operation. ICC 100 lite is suitable for tempering liquids up to 100 °C and internal circulation.

To make configuration of your temperature control system as convenient as possible, IKA offers "ready-to-connect" packages with all the necessary accessories.

Package includes:



ICC 100 lite Compact immersion circulator IB 8 eco Plastic bath (size S)
BS.ICC lite Bath bridge, small

Max. temperature in the plastic bath (eco): 100 °C (water only)
Technical data relates to the temperature control instrument included in the package.



Technical Data

| Appliance type | Compact immersion circulators |
|---|-------------------------------|
| Class designation acc. DIN 12876 | |
| Identification according to DIN 12876 | FL |
| Heat output [W] | 2000 |
| Working temperature [°C] | room temp 100 |
| Operating temperature min. (with external cooling) [°C] | -25 |
| Temperature display | yes |
| Temperature control | PID |
| Working temperature sensor | PT1000 |
| Safety temperature sensor | PT1000 |
| Working temperature display | LED |
| Safety temperature display | LED |
| Temperature stability DIN 12876 [K] | ±0.05 |
| Display resolution [K] | 0.1 |
| Set temperature resolution [K] | ±0.1 |
| Warning function optical | yes |
| Warning function acoustic | yes |
| Adjustable safety circuit [°C] | 0 - 110 |
| Sub-level protection | yes |
| Bath depth min. [mm] | 150 |
| Calibration option | yes |
| Appliance fastener | clamp |
| Technical data complies with the standard | DIN 12876 |
| Permissible ON time [%] | 100 |
| Dimensions (W x H x D) [mm] | 135 x 303 x 180 |
| Weight [kg] | 4.2 |
| Permissible ambient temperature [°C] | 5 - 40 |
| Permissible relative humidity [%] | 80 |
| Protection class according to DIN EN 60529 | IP 21 |
| RS 232 interface | yes |
| USB interface | USB-B |
| Voltage [V] | 230 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 2100 |



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.