


3-4 (oil-lubricated)

Voltage	V	100	100	120	200	200	230	230					
Frequency	Hz	50	60	60	50	60	50	60					
Motor	HP	0.20	0.20	0.20	0.18	0.18	0.18	0.18					
	kW	0.15	0.15	0.15	0.13	0.13	0.13	0.13					
Displacement	l/min	17	20	20	17	20	17	20					
	CFM	0.60	0.71	0.71	0.60	0.71	0.60	0.71					
FAD @ 8 bar	l/min	11	13	13	11	13	11	13					
	CFM	0.39	0.46	0.46	0.39	0.46	0.39	0.46					
Max. pressure ¹⁾	bar	8	8	8	8	8	8	8					
	psi	120	120	120	120	120	120	120					
Max. current	A	2.8	2.7	2.4	0.9	0.9	0.9	0.9					
Tank size	litres	4	4	4	4	4	4	4					
	gallon	1.1	1.1	1.1	1.1	1.1	1.1	1.1					
Weight	kg	18	18	18	18	18	18	18					
	lbs	40	40	40	40	40	40	40					
Noise level	dB(A)/1m	35	35	35	35	35	35	35					
Thermal protection		Yes	Yes	Yes	Yes	Yes	Yes	Yes					
Duty cycle		50%	50%	50%	50%	50%	50%	50%					



Dimensions (l x w x h)
382 x 300 x 334 mm / 15 x 11 6/8 x 13 1/8 inch

¹⁾ Higher pressure available upon request

Technical modifications reserved



JUN-AIR®



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

