

TRANSFER PUMP FOR LIQUIDS

LIQUIPORT 300, 1.300



Hydraulic data

Detergents

Туре	Flow rate	Suction height	Max. pressure
LIQUIPORT 300	0.5–3.0 l/min	3 mWg	1 bar
LIQUIPORT 1.300	0.5–3.0 l/min	3 mWg	4 bar

Chemical resistance

Code	Pump head	Diaphragm	Valves
KT	PP	PTFE covered	FFKM
TT	PVDF	PTFE covered	FFKM
FT	PTFE	PTFE covered	FFKM

Functions

S - Version	RC - Version		
Manual operation	 Manual operation Analog control: 0–10 V from 0 to 100% (other on request) Start/Stop through logic control (TTL) 	Output signal fault alarmCable for external control included	

Technical data

- Main supply 100–240 V / 50–60 Hz
- Ambient temperature allowed +5 to +40 °C
- Liquid temperature allowed +5 to +80 °C
- Maximum viscosity allowed 150 cSt
- Power consumption 29-34 W

- Protection class IP65
- Dimensions: 160 x 104 x 188 mm
- Weight: 1.5 kg
- Supply with barbed fittings: for tubing ID 12 mm

ACCESSORIES

LIQUIPORT 300, 1.300

Mounting plate

	ID-Nr.
for wall mounting	160473



Standfitting

ID-Nr.
160474



Footswitch

	ID-Nr.
for impulse start and stop	155872





Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.