KERN KDP 300-3-2022e



Universal weighing platforms for flexible connection in process chains



Category	
Brand	KERN
Product categoriy	Component
Product group	Digital platform
Product family	KDP

Measuring System	
Weighing system	Strain gauge
Weighing capacity [Max]	350 g
Readability [d]	1 mg
Reproducibility	2 mg
Linearity	± 5 mg
Resolution	350.000
Adjustment options	Adjusting with external weight
Recommended adjusting weight	350 g (F1)
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	5 mg
Maximum creep (15 minutes)	10 mg
Maximum creep (30 minutes)	20 mg
Default unit	g

Construction	
Dimension housing (W×D×H)	165×166×75 mm
Dimensions completely mounted (W×D×H)	165×166×140 mm
Dimensions rectangular draught shield - inner (W×D×H)	146×146×80 mm
Dimensions rectangular draught shield - outer (W×D×H)	157×157×80 mm
Dimension display device (W×D×H)	0×0×0 mm
Dimensions weighing surface (\emptyset)	105 mm

Dimensions weighing surface	105 mm	
Dimensions weighing platform (W×D×H)	165×165×73 mm	
Material weighing plate	plastic, with conductive lacquer	
Material platform	Plastics	
Material display housing	No display available	
Level indicator	✓	
Levelling feet adjustable	✓	
Cable length	1,2 m	
Display device cable length	1,5 m	

Functions	
IP protection - display	no IP protection
Auto-off interval(s) in mains power mode	off

Interface	
Interfaces	Ethernet (optional, factory) WiFi (optional, factory) Bluetooth BLE (v4.0) (optional, factory) USB-Device
EasyTouch (ET) - Compatibility	vollständig
EasyTouch (ET) - Connection type	über alle verfügbare Schnittstellen möglich

Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	USB including power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	5 V, 1 A

Environmental conditions		
Ambient temperature [Min]	5 °C	
Ambient temperature [Max]	35 °C	
Humity of environment [Max]	80 %	
Approval		

CE mark

1

KERN KDP 300-3-2022e



Universal weighing platforms for flexible connection in process chains

969-517

Services (optional)

Article number for DAkkS 963-127 calibration

Article number for certificate of

conformity (verification)

Packing & Shipping

Delivery time 1 d

250×525×165 mm Dimensions packaging (W×D×H) Shipping method Parcel service Net weight approx. 1,2 kg

Gross weight approx. 2,0 kg Shipping weight 4,3 kg

Pictograms

STANDARD



OPTION



FACTORY







Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.