

Compact laboratory balance KERN PCD



BASIC  
★

EasyTouch



High-resolution precision balance with removable display for maximum flexibility

**Features**

- Laboratory balance with separate platform: Ideal when working in a glove bag or fume cupboard. Particularly practical for weighing toxic, volatile or contaminated substances
- PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels
- Freely programmable weighing unit, e.g. display direct in special units such as length of thread g/m, paper weight g/m<sup>2</sup>, or similar
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard, to give the most accurate weighing result
- **1** Draught shield standard for models with weighing plate size **A**, weighing space W×D×H 146×146×80 mm
- Protective working cover included with delivery

**Technical data**

- Large backlit LCD display, digit height 21 mm
- Dimensions weighing surface
  - A** ø 105 mm
  - B** W×D, see larger picture
- Weighing plate material
  - A** plastic, with conductive lacquer
  - B** Stainless Steel
- Dimensions of display device W×D×H 165×280×141 mm
- Optional battery operation, 9 V block not included in scope of delivery, operating time up to 12 h, AUTO-OFF function to preserve the battery
- Overall dimensions W×D×H, without draught shield 165×280×75 mm
- Cable length of display device approx. 1,2 m
- Net weight approx. 1,2 kg
- Permissible ambient temperature 5 °C/35 °C

**Accessories**

- Protective working cover over the display device, scope of delivery: 5 items, KERN PCD-A05S05
- **2** Stand to elevate display device, height of stand approx. 250 mm, KERN PCD-A03
- Internal rechargeable battery pack, operating time up to 24 h without backlight, charging time approx. 10 h, KERN PCD-A04
- **3** Foot switch, ideal when the application requires two free hands. TARE or PRINT function can be selected. Scope of delivery: foot switch, junction box, connection cable. For the PRINT function you will need the RS-232 interface cable, KERN YKF-01
- RS-232/Ethernet adapter for connection to an IP-based Ethernet network, KERN YKI-01
- Individual header data: the free software can be used to print 4 header lines on the printout when using printers 911-013, YKN-01, YKB-01N and YKE-01 (in combination with YKI-02)
- Further details, plenty of further accessories and suitable printers see *Accessories*

STANDARD



OPTION



| Model      | Weighing capacity [Max] g | Readability [d] g | Reproducibility g | Linearity g | Weighing plate | Option                    |            |
|------------|---------------------------|-------------------|-------------------|-------------|----------------|---------------------------|------------|
|            |                           |                   |                   |             |                | DAkKS Calibr. Certificate | DAkKS KERN |
| PCD 250-3  | 250                       | 0,001             | 0,002             | ± 0,005     | <b>A</b>       | 963-127                   |            |
| PCD 300-3  | 350                       | 0,001             | 0,002             | ± 0,005     | <b>A</b>       | 963-127                   |            |
| PCD 2500-2 | 2500                      | 0,01              | 0,02              | ± 0,05      | <b>B</b>       | 963-127                   |            |
| PCD 3000-2 | 3500                      | 0,01              | 0,02              | ± 0,05      | <b>B</b>       | 963-127                   |            |
| PCD 6K-4   | 6000                      | 0,1               | 0,1               | ± 0,3       | <b>B</b>       | 963-128                   |            |
| PCD 10K0.1 | 10000                     | 0,1               | 0,1               | ± 0,3       | <b>B</b>       | 963-128                   |            |
| PCD 10K-3  | 10000                     | 1                 | 1                 | ± 3         | <b>B</b>       | 963-128                   |            |

## Pictograms

|  |  |  |
|--|--|--|
| <p><b>Internal adjusting:</b><br/>Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)</p>  | <p><b>KERN Communication Protocol (KCP):</b><br/>It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems</p> | <p><b>Suspended weighing:</b><br/>Load support with hook on the underside of the balance</p>   |
| <p><b>Adjusting program CAL:</b><br/>For quick setting up of the balance's accuracy. External adjusting weight required</p>  | <p><b>GLP/ISO log:</b><br/>The balance displays serial number, user ID, weight, date and time, regardless of a printer connection</p>  | <p><b>Battery operation:</b><br/>Ready for battery operation. The battery type is specified for each device</p>  |
| <p><b>Easy Touch:</b><br/>Suitable for the connection, data transmission and control through PC or tablet.</p>   | <p><b>GLP/ISO log:</b><br/>With weight, date and time. Only with KERN printers.</p>  | <p><b>Rechargeable battery pack:</b><br/>Rechargeable set</p>  |
| <p><b>Memory:</b><br/>Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.</p>  | <p><b>Piece counting:</b><br/>Reference quantities selectable. Display can be switched from piece to weight</p>  | <p><b>Universal plug-in power supply:</b><br/>with universal input and optional input socket adapters for A) EU, CH, GB; B) EU, CH, GB, USA; C) EU, CH, GB, USA, AUS</p> |
| <p><b>Alibi memory:</b><br/>Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.</p>  | <p><b>Recipe level A:</b><br/>The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out</p>  | <p><b>Plug-in power supply:</b><br/>230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available</p>  |
| <p><b>Data interface RS-232:</b><br/>To connect the balance to a printer, PC or network</p>  | <p><b>Recipe level B:</b><br/>Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display</p>   | <p><b>Integrated power supply unit:</b><br/>Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request</p>                              |
| <p><b>RS-485 data interface:</b><br/>To connect the balance to a printer, PC or other peripherals. Suitable for datatransfer over large distances. Network in bus topology is possible</p> | <p><b>Totalising level A:</b><br/>The weights of similar items can be added together and the total can be printed out</p>  | <p><b>Weighing principle: Strain gauges:</b><br/>Electrical resistor on an elastic deforming body</p>  |
| <p><b>USB data interface:</b><br/>To connect the balance to a printer, PC or other peripherals</p>   | <p><b>Percentage determination:</b><br/>Determining the deviation in % from the target value (100 %)</p>   | <p><b>Weighing principle: Tuning fork:</b><br/>A resonating body is electromagnetically excited, causing it to oscillate</p>   |
| <p><b>Bluetooth* data interface:</b><br/>To transfer data from the balance to a printer, PC or other peripherals</p>   | <p><b>Weighing units:</b><br/>Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details</p>  | <p><b>Weighing principle: Electromagnetic force compensation:</b><br/>Coil inside a permanent magnet. For the most accurate weighings</p>                                |
| <p><b>WiFi data interface:</b><br/>To transfer data from the balance to a printer, PC or other peripherals</p>   | <p><b>Weighing with tolerance range:</b><br/>(Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model</p>   | <p><b>Weighing principle: Single cell technology:</b><br/>Advanced version of the force compensation principle with the highest level of precision</p>                   |
| <p><b>Control outputs (optocoupler, digital I/O):</b><br/>To connect relays, signal lamps, valves, etc.</p>  | <p><b>Hold function:</b><br/>(Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value</p>  | <p><b>Verification possible:</b><br/>The time required for verification is specified in the pictogram</p>  |
| <p><b>Analogue interface:</b><br/>to connect a suitable peripheral device for analogue processing of the measurements</p>  | <p><b>Protection against dust and water splashes IPxx:</b><br/>The type of protection is shown in the pictogram.</p>   | <p><b>DAKkS calibration possible (DKD):</b><br/>The time required for DAKkS calibration is shown in days in the pictogram</p>  |
| <p><b>Interface for second balance:</b><br/>For direct connection of a second balance</p>  |  | <p><b>Factory calibration (ISO):</b><br/>The time required for Factory calibration is shown in days in the pictogram</p>   |
| <p><b>Network interface:</b><br/>For connecting the scale to an Ethernet network</p>   |  | <p><b>Package shipment:</b><br/>The time required for internal shipping preparations is shown in days in the pictogram</p>   |
|  |  | <p><b>Pallet shipment:</b><br/>The time required for internal shipping preparations is shown in days in the pictogram</p>  |

\*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.

## KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

### Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg - 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, EN, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

## Your KERN specialist dealer:



# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.