KERN OBN 135T241



The digital laboratory assistant with infinity optical unit and professional Koehler illumination



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Digital microscope set
Product family	OBN-S
Display	
	0040-450/
Display resolution	2048×1536
Construction	
Dimension (W×D×H)	390×235×620 mm
Optical system	Infinity
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	1
Tube type	Siedentopf
Light distribution	100:0
Contrasting methods	Bright field Darkfield (optional) Polarisation (optional) Fluorescent (optinal) Phase contrast (optional)
Standard objectives	4× 10× 20× 40× 100×
Lens quality	Infinity Plan
Nosepiece screw-in locations	5
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5

Diopter adjustment [Max]	5
C-Mount magnification	0,5 x
C-Mount focusable	✓
Supported camera types	Microscope Camera
Functions	
Camera - Applicable software	integrated
Supported operating systems	Android
Memory - total size	128 GB
Interface	
Interfaces	WiFi standard USB 2.0 HDMI MicroSD card slot
Ocular	
Ocular field width	HWF
Ocular magnifications	10 x
Ocular visual field	20 mm
Ocular diameter	23,2 mm
Illumination	
Illuminance	Transmitted light
Illumination type incident light	Transmitted light none
Illumination type incident light	none
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted	none LED
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light	none LED 3 W
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination	none LED 3 W
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible	none LED 3 W
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm	none LED 3 W
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm	none LED 3 W ✓ ✓ ✓
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm Field of view [Min]	none LED 3 W ✓ ✓ ✓ ✓ ✓
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm Field diaphragm Field of view [Min] Field of view [Max]	none LED 3 W ✓ ✓ ✓ ✓ ✓ ✓ ✓ Ø,2 mm 5 mm
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm Field diaphragm Field of view [Min] Field of view [Max] Torque regulation	none LED 3 W ✓ ✓ ✓ ✓ O,2 mm 5 mm
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm Field diaphragm Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum	none LED 3 W ✓ ✓ ✓ ✓ ✓ Ø,2 mm 5 mm ✓ Ø,002 mm
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm Field diaphragm Field of view [Min] Field of view [Max] Torque regulation	none LED 3 W ✓ ✓ ✓ ✓ O,2 mm 5 mm
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm Field diaphragm Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum	none LED 3 W ✓ ✓ ✓ ✓ Ø,2 mm 5 mm ✓ 0,002 mm coaxial coarse and fine
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm Field diaphragm Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum	none LED 3 W ✓ ✓ ✓ ✓ Ø,2 mm 5 mm ✓ 0,002 mm coaxial coarse and fine
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm Field diaphragm Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism	none LED 3 W ✓ ✓ ✓ ✓ Ø,2 mm 5 mm ✓ 0,002 mm coaxial coarse and fine
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm Field diaphragm Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism	none LED 3 W ✓ ✓ ✓ ✓ 0,2 mm 5 mm ✓ 0,002 mm coaxial coarse and fine drive
Illumination type incident lightIllumination type transmitted lightIllumination intensity transmittedlightKoehler illuminationFilter possibleAperture diaphragmField diaphragmField of view [Min]Field of view [Max]Torque regulationFine drive minimumFocusing mechanismCameraCameratype	none LED 3 W ✓ ✓ ✓ ✓ ✓ Ø,2 mm 5 mm ✓ Ø,002 mm coaxial coarse and fine drive Tablet camera
Illumination type incident light Illumination type transmitted light Illumination intensity transmitted light Koehler illumination Filter possible Aperture diaphragm Field diaphragm Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism Cameratype Camera - Adapter type	none LED 3 W ✓ ✓ ✓ ✓ Ø,0 02 mm coaxial coarse and fine drive Tablet camera C-Mount

KERN OBN 135T241



The digital laboratory assistant with infinity optical unit and professional Koehler illumination

Camera - Colour depth	Colour
Camera - Framerate	30 fps
Camera- Mounting types	C-mount thread
Camera - Exposure method	Rolling Shutter
Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Built-in power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO
	AUS
Plug-in power supply / adapter for	UK
countries - optional	US CH
Input voltage power supply /	GH
power [Max]	100 - 240 V
Input voltage device / power [Max]	100 - 240 V
Environmental conditions	
Environmental conditions	
Storage temperature [Min]	-5 °C
	-5 °C 40 °C
Storage temperature [Min] Storage temperature [Max]	
Storage temperature [Min]	
Storage temperature [Min] Storage temperature [Max]	
Storage temperature [Min] Storage temperature [Max] Approval	40 °C
Storage temperature [Min] Storage temperature [Max] Approval CE mark	40 °C
Storage temperature [Min] Storage temperature [Max] Approval CE mark Packing & Shipping	40 °C ✓
Storage temperature [Min] Storage temperature [Max] Approval CE mark Packing & Shipping Delivery time	40 °C ✓ 1 d
Storage temperature [Min] Storage temperature [Max] Approval CE mark Packing & Shipping Delivery time Dimensions packaging (W×D×H)	40 °C ✓ 1 d 590×440×390 mm
Storage temperature [Min] Storage temperature [Max] Approval CE mark Packing & Shipping Delivery time Dimensions packaging (W×D×H) Net weight	40 °C ✓ 1 d 590×440×390 mm 10,973 kg
Storage temperature [Min] Storage temperature [Max] Approval CE mark Packing & Shipping Delivery time Dimensions packaging (W×D×H) Net weight Shipping method	40 °C ✓ ✓ 1 d 590×440×390 mm 10,973 kg Parcel service
Storage temperature [Min] Storage temperature [Max] Approval CE mark Packing & Shipping Delivery time Dimensions packaging (W×D×H) Net weight Shipping method Net weight approx.	40 °C ✓ ✓ 1 d 590×440×390 mm 10,973 kg Parcel service 11 kg



Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.