# Pharmacy Plus Bluetooth Enabled Refrigerator

# 400L Pharmacy Plus Upright Fridge with Glass Door and Digital Lock

GDMAcode	
SKU code	

PPGR400BT-DLK 444411395





#### Key features

- ✓ Local monitoring and alarm history via Bluetooth
- $\checkmark$  Power failure alarm with backup battery powered recording
- $\checkmark$  Solid and glass door options

 $\checkmark$  Intelligent fan management system for enhanced performance



#### Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of power outage.



#### Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.



#### Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.



#### Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

### Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



#### Specification: 400L Pharmacy Plus Upright Fridge with Glass Door and Digital Lock

oss Capacity (litres) at Capacity (litres) hit External Width (mm) hit External Depth (mm) hit External Height (mm) oduct Weight (kg) hicked Width (mm) hit External Height (mm)	394L 389L 595mm 660mm 1935mm
nit External Width (mm) nit External Depth (mm) nit External Height (mm) oduct Weight (kg) ncked Width (mm)	595mm 660mm
nit External Depth (mm) nit External Height (mm) oduct Weight (kg) Icked Width (mm)	660mm
nit External Height (mm) oduct Weight (kg) Icked Width (mm)	
oduct Weight (kg) acked Width (mm)	1955mm
ncked Width (mm)	69.6Kg
	640mm
	660mm
ncked Height (mm)	1995mm
icked Weight (kg)	78.6Kg
puntry of Origin	UK
ternal Dimensions (mm) (WxDxH)	515mm x 480mm x 1783mm
mperature Range	+2°C to +8°C
blour	White/green
iternal Finish	Painted Steel
ternal Finish	HIPS*
pe of plastic	SRL800 (HIPS/ABS mix)
pe of plastic	PVC / Glass
por Type	Glass
por Style	Hinged, right handed only, non-reversible
por Liner	
umber of Door Trays	Flat n/a
umber of Door Trays umber of Door Tray Positions	
-	n/a 1150mm
bor Open Depth (mm)	1150mm
eplacement Door Seal	Yes
ben Door Sensor	Yes 2 Varia
ck	Yes, 2 Keys
ljustable Feet (number & position)	2 adjustable (front)
orthole	Yes
orthole Size	16 mm
orthole Location	Rear Bottom
mperature Display on Panel	Yes
mperature Alarm	Yes
emote Alarm Contacts	Yes
udible Alarms	Yes
sual Alarms	Yes
umber of Shelves/Drawers	7
umber of Shelf Positions	12
uelf Size (mm) (WxDxH)	496mm x 405mm x 6mm
elf Material	Polythene Coated Wire
rawer Size (mm) (WxDxH)	n/a
rawer Material	n/a
umber of Baskets	]
asket Material	Polythene Coated Wire
asket Size (mm) (WxDxH)	485mm x 255mm x 171mm
terior Light	Yes
ght Type	LED
ght Activation	Door Switch / Controller
n	Yes - Tangential
bark Free	no
efrost setting	Auto (Off Cycle)
ontroller Type	Digital BT, External
ttery Back Up/Hours	no
uetooth	Yes
=C	Yes
IFI	no
umber of Probes	2
ове Туре	Air & Load (Silicone Oil)
nbient Temperature Range	10°C to 32°C
frigerant Type	R600a
C Free	Yes
C Free	Yes
CFC Free	Yes
nmonia Free	Yes
( 3 Pin Plug	no
-	Yes
her Plug Types Available	
cher Plug Types Available	45mm
ltage Supply	
oltage Supply sulation Thickness (mm)	
oltage Supply sulation Thickness (mm) sulation Type	High Density Polyurethane Foam
oltage Supply sulation Thickness (mm) sulation Type owing Agent	High Density Polyurethane Foam Cyclopentane
oltage Supply sulation Thickness (mm) sulation Type owing Agent nti Microbial Handle	High Density Polyurethane Foam Cyclopentane Yes
oltage Supply sulation Thickness (mm) sulation Type owing Agent nti Microbial Handle all Brackets	High Density Polyurethane Foam Cyclopentane Yes no
oltage Supply sulation Thickness (mm) sulation Type owing Agent nti Microbial Handle all Brackets otional Drawer System	High Density Polyurethane Foam Cyclopentane Yes no no no
oltage Supply sulation Thickness (mm) sulation Type owing Agent nti Microbial Handle all Brackets	High Density Polyurethane Foam Cyclopentane Yes no

The Experts in Medical Refrigeration





Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

# www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.