Pharmacy Plus Bluetooth Enabled Refrigerator

310L Pharmacy Plus Upright Fridge with Solid Door with Digital Lock

GDMAcode PPSR310BT-DLK

SKU code 444411391







Key features

- ✓ Local monitoring and alarm history via Bluetooth
- ✓ Power failure alarm with backup battery powered recording
- √ Solid and glass door options
- ✓ Intelligent fan management system for enhanced performance



4.3° - 4.3° - 4.1°







Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



Specification: 310L Pharmacy Plus Upright Fridge with Solid Door and Digital Lock

Gross Capacity (litres)	310L
Net Capacity (litres)	305L
Unit External Width (mm)	595mm
Unit External Depth (mm)	660mm
Unit External Height (mm)	1560mm
Product Weight (kg)	50.0Kg
Packed Width (mm)	640mm
Packed Depth (mm)	660mm
Packed Height (mm)	1560mm
Packed Weight (kg)	57Kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	515mm x 480mm x 1415mm
Temperature Range	+2°C to +8°C
Colour	White/green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Flat
Number of Door Trays	n/a
Number of Door Tray Positions	n/a
Door Open Depth (mm)	1150mm
Replacement Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 adjustable (front)
Porthole	Yes
Porthole Size	16 mm
Porthole Location	Rear Bottom
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	5
Number of Shelf Positions	9
	496mm x 405mm x 6mm
Shelf Size (mm) (WxDxH) Shelf Material	Polythene Coated Wire
Drawer Size (mm) (WxDxH)	
	n/a
Drawer Material Number of Baskets	n/a
	Polythene Coated Wire
Basket Material	
Basket Size (mm) (WxDxH)	485mm x 255mm x 171mm
Interior Light	Yes
Light Type	LED Dear Control / Constroller
Light Activation	Door Switch / Controller
Fan	Yes - Tangential
Spark Free	No
Defrost setting	Auto (Off Cycle)
Controller Type	Digital BT, External
Battery Back Up/Hours	No V
Bluetooth	Yes
NFC	Yes
	k i
WIFI	No
WIFI Number of Probes	2
WIFI Number of Probes Probe Type	2 Air & Load (Silicone Oil)
WIFI Number of Probes Probe Type Ambient Temperature Range	2 Air & Load (Silicone Oil) 10°C to 32°C
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type	2 Air & Load (Silicone Oil) 10°C to 32°C R600a
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes Yes No
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes No Yes
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes Yes No
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes Yes No Yes
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes No Yes 220-240V
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm)	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes 220-240V 45mm
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes And No Yes 220-240V 45mm High Density Polyurethane Foam
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes And No Yes 220-240V 45mm High Density Polyurethane Foam Cyclopentane
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes Ano Yes No Yes 220-240V 45mm High Density Polyurethane Foam Cyclopentane Yes
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets Optional Drawer System	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes Ano Yes Ano Yes Ano Yes Cyclopentane Yes No
WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets	2 Air & Load (Silicone Oil) 10°C to 32°C R600a Yes Yes Yes Yes Yes No Yes S20-240V 45mm High Density Polyurethane Foam Cyclopentane Yes No No No No No No





Wolflabs

www.wolflabs.co.uk











Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed, please provide these to our sales team so that details can be confirmed.





