Bluetooth Enabled Pharmacy Plus Range

158L Bluetooth Pharmacy Under Counter Fridge

GDPA code PPSR158BT-UK

SKU code 444411308









Key features

- ✓ Local Monitoring and Alarm History via Bluetooth
- ✓ Power Failure Alarm with battery back up. Rechargeable battery
- Solid and glass door options
- ✓ Intelligent Fan Management for Enhanced Performance



New Controller

Offers Local
temperature
monitoring and alarm
history via Bluetooth.
Power failure alarm
with battery backup,
rechargeable battery
and intelligent
fan management
for enhanced
performance



New Bluetooth Enabled App

Accessibility features include contactless local monitoring of air and load temperatures.

Downloadable temperature history and alarm history.



Flexible internal storage

Multiple shelf locations along with a wire basket provides a flexible storage solution.



Anti-microbial handle

Powder coated to help prevent cross contamination by inhibiting the growth of microbes.



Dual probe

Greater temperature accuracy given from two temperature probe readings. One probe measuring air temperature and one measuring load (or product) temperature.

Section	
Unit External Width (mm)595mmUnit External Depth (mm)660mmUnit External Height (mm)850mmProduct Weight (kg)33.25kgPacked Width (mm)640mmPacked Depth (mm)660mmPacked Height (mm)910mmPacked Weight (kg)37.82kgCountry of OriginUKInternal Dimensions (mm) (WxDxH)500mm W x 450mm D x 725mm HTemperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor TypeHinged, reversibleDoor StyleHinged, reversibleDoor Open Depth (mm)1150mmReplacement Door SealYes	
Unit External Depth (mm)660mmUnit External Height (mm)850mmProduct Weight (kg)33.25kgPacked Width (mm)640mmPacked Depth (mm)660mmPacked Height (mm)910mmPacked Weight (kg)37.82kgCountry of OriginUKInternal Dimensions (mm) (WxDxH)500mm W x 450mm D x 725mm HTemperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Unit External Height (mm)850mmProduct Weight (kg)33.25kgPacked Width (mm)640mmPacked Depth (mm)660mmPacked Height (mm)910mmPacked Weight (kg)37.82kgCountry of OriginUKInternal Dimensions (mm) (WxDxH)500mm W x 450mm D x 725mm HTemperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Product Weight (kg)33.25kgPacked Width (mm)640mmPacked Depth (mm)660mmPacked Height (mm)910mmPacked Weight (kg)37.82kgCountry of OriginUKInternal Dimensions (mm) (WxDxH)500mm W x 450mm D x 725mm HTemperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Packed Width (mm)640mmPacked Depth (mm)660mmPacked Height (mm)910mmPacked Weight (kg)37.82kgCountry of OriginUKInternal Dimensions (mm) (WxDxH)500mm W x 450mm D x 725mm HTemperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Packed Depth (mm)660mmPacked Height (mm)910mmPacked Weight (kg)37.82kgCountry of OriginUKInternal Dimensions (mm) (WxDxH)500mm W x 450mm D x 725mm HTemperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Packed Height (mm)910mmPacked Weight (kg)37.82 kgCountry of OriginUKInternal Dimensions (mm) (WxDxH)500mm W x 450mm D x 725mm HTemperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Packed Weight (kg)37.82kgCountry of OriginUKInternal Dimensions (mm) (WxDxH)500mm W x 450mm D x 725mm HTemperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Country of OriginUKInternal Dimensions (mm) (WxDxH)500mm W x 450mm D x 725mm HTemperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Internal Dimensions (mm) (WxDxH)500mm W x 450mm D x 725mm HTemperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Temperature Range2°C to 8°CColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
ColourWhite/greenExternal FinishPainted SteelInternal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
External Finish Painted Steel Internal Finish HIPS* Type of plastic SRL800 (HIPS/ABS mix) Door Finish Painted Steel / Solid Door Type Solid Door Style Hinged, reversible Door Liner Flat Door Open Depth (mm) 1150mm Replacement Door Seal Yes	
Internal FinishHIPS*Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Type of plasticSRL800 (HIPS/ABS mix)Door FinishPainted Steel / SolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Door FinishPainted Steel / SolidDoor TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Door TypeSolidDoor StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Door StyleHinged, reversibleDoor LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Door LinerFlatDoor Open Depth (mm)1150mmReplacement Door SealYes	
Door Open Depth (mm) 1150mm Replacement Door Seal Yes	
Replacement Door Seal Yes	
·	
Open Door Sensor Yes	
Lock Yes, 2 Keys	
Adjustable Feet (number & position) 4 All adjustable	
Porthole Yes	
Porthole Size 16 mm	
Porthole Location Rear Bottom	
Temperature Display on Panel Yes	
Temperature Alarm Yes	
Remote Alarm Contacts Yes	
Audible Alarms Yes	
Visual Alarms Yes	
Number of Shelves 4	
Number of Shelf Positions 5	
Shelf Size (mm) (WxDxH) 496mm W x 405mm D x 6mm H	
Shelf Material Polythene Coated Wire	
Number of Baskets	
Basket Material Polythene Coated Wire	
Basket Size (mm) (WxDxH) 485mm W x 255mm D x 171mm H	
Interior Light Yes	
LED LED	
Light Activation Door Swith / Controller	
Fan Yes - Tangential	
Spark Free No	
Defrost setting Auto (Off Cycle)	
Defrost setting Auto (Off Cycle) Controller Type Digital BT, external	
Controller TypeDigital BT, externalNumber of Probes2	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°C	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600a	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYes	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYes	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYes	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYes	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNo	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYes	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220 -240V	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220 -240VInsulation Thickness (mm)45mm	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220 -240VInsulation Thickness (mm)High Density Polyurethane Foam	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220 -240VInsulation Thickness (mm)45mm	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220 -240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane Foam	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220 -240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentane	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220 -240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYes	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220 -240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNo	
Controller TypeDigital BT, externalNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220 -240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemNo	



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.