

# Eutech DO 450



## Dissolved Oxygen / Temperature

Affordable optical RDO technology reduces maintenance time and costs

- Maintenance free optical probe with no electrolyte eliminates hassle of replacing delicate membranes and salt build up from refilling solutions
- Durable waterproof and dustproof design with IP67 rating
- Large, backlit custom display provides measurement with temperature
- Switch between % saturation and mg/L (ppm) dissolved oxygen with a press of a button
- **Calibration due alarm** – Set a visible reminder when it is time to recalibrate the meter
- Manual barometric pressure and salinity correction
- **Selectable °C or °F** – Choose the unit to best fit your application
- Ready indicator, manual or automatic measurement hold feature and optional automatic shutoff function
- **Store up to 500 data sets** – Easy USB or RS232 output with optional data cables
- **Built-in real-time clock stamps stored data and calibration data with time and date** – Meets standards for GLP (Good Laboratory Practices)
- 500 hours battery life or use optional universal power adapter
- **Built-in stand with wall-mount** – Allows for easy benchtop measurement and storage



Calibration Chamber



RDO Weight/Guard



RDO Sensor Cap



RDO Probe



## Specification Table

<b>Dissolved Oxygen</b>	Range	0 to 200 %; 0 to 20 ppm/mg/L
	Resolution	0.10 %; 0.1 ppm/mg/L
	Accuracy	±2 %; ±0.1 ppm or mg/L up to 8; ±0.2 ppm or mg/L above 8
	Calibration	Zero and saturation
<b>Temperature</b>	Range	0.0 to 50.0 °C (0.0 to 122.0 °F)
	Resolution	0.1 °C/°F
	Accuracy	±0.5 °C; ±0.9 °F
	Calibration	Offset in 0.1 increments, ±10 °C or ±18 °F
<b>Display</b>	Custom LCD with backlight	
<b>Memory</b>	Stores up to 500 data sets	
<b>Output</b>	USB or RS232	
<b>Real-Time Clock</b>	Time and date stamp on calibration and stored data	
<b>Temperature Compensation</b>	Yes	
<b>Pressure &amp; Salinity Compensation</b>	Manual	
<b>Power</b>	Two AA batteries (included), >100 hours (without backlight); AC adapter (optional)	



## Ordering Information

Order Code	Part No.	Description
<b>Meter</b>		
ECDOWP45000	01X651634	<b>DO 450 Meter Only:</b> Meter, two AA batteries
ECDOWP45003	01X651644	<b>DO 450 Meter &amp; Electrode:</b> Meter, RDO electrode with sensor cap, two AA batteries
ECDOWP45003K	01X651635	<b>DO 450 Meter Kit:</b> Meter, RDO electrode with sensor cap, two AA batteries, hard carry case, USB cable, RDO stainless steel weight/guard, RDO calibration chamber
<b>Electrodes</b>		
RDO3M	RDO3M	RDO probe, 3 m (10 ft) cable
RDO6M	RDO6M	RDO probe, 6 m (20 ft) cable
RDO15M	RDO15M	RDO probe, 15 m (50 ft) cable
<b>Accessories</b>		
RDOCAP	RDOCAP	Replacement RDO sensor cap
RDOWEIGHT	RDOWEIGHT	RDO weight/guard, screw thread to attach to probe
RDOCALCHAMBER	RDOCALCHAMBER	Calibration chamber
60X426401	60X426401	Optional 100 / 240 VAC SMPS power adapter, 9V, 6 W
MINIPHONEUSB	MINIPHONEUSB	USB cable for 450 series, mini phone plug to USB
30X427301	30X427301	RS232 cable for 450 series, mini phone plug to RS232 9-pin (F)
ECDOZEROSOLN	01X211238	Zero oxygen solution, 0 % DO, 480 mL

# Comparison Tables



Meter Features	pH 150	CON 150	pH 450	CON 450	DO 450	PD 450	PC 450
	See Page 4	See Page 5	See Page 6	See Page 7	See Page 8	See Page 9	See Page 10
pH & mV	✓	-	✓	-	-	✓	✓
ION	-	-	✓	-	-	-	-
Temperature	✓	✓	✓	✓	✓	✓	✓
Conductivity & TDS	-	✓	-	✓	-	-	✓
Optical Dissolved Oxygen	-	-	-	-	✓	✓	-
Salinity	-	-	-	✓	-	-	-
Display	Three line custom LCD			Three line custom LCD with backlight			
Temperature Compensation	Automatic or manual from -10 to 110 °C						
Temperature Coefficient	-	0.00 to 10.00 %/°C	-	0.00 to 10.00 %/°C	-	-	0.00 to 10.00 %/°C
Memory	150 data sets				500 data sets		
Output	-				USB or RS232		
Real-Time Clock	Time and date stamp on calibration and stored data						
Power	Two AA batteries (included)						
	>700 hours continuous use	>500 hours continuous use	>500 hours (without backlight)	>300 hours (without backlight)	>100 hours (without backlight)		
Dimensions (L x W x H)	Meter: 7 1/8" x 3 1/8" x 2 1/4" (20 x 8.3 x 5.7 cm) ; Boxed: 9 1/8" x 9 1/8" x 2 3/4" (23 x 23 x 7 cm)						
Weight	Meter: 1 lb (0.5 kg) ; Boxed: 1.4 lb (0.7 kg)						

Eutech 150 Series & Eutech 450 Series Configurations		Electrodes						Accessories				Solutions	
		Double-Junction pH Electrode (ECFC725201B)	pH Electrode, 26 mm Diameter (ECDA9350603B)	Combi pH/Con/ATC Electrode (COMBI03BW)	Conductivity/ATC Electrode, K = 1 (CONSEN91W)	ATC Probe (PHWPTEM01W)	RDO Electrode With Cap (RDO3M)	Glip-Clip™	Hard Carry Case	USB Cable	RDO Stainless Steel Weight/Guard	RDO Calibration Sleeve	60 mL Bottles of pH 4, pH 7, Storage Solution, DI Water
Order Code	Product Combination												
ECPHWP15000	pH 150 Meter Only						✓						
ECPHWP15002	pH 150 Meter & Electrode	✓				✓	✓						
ECPHWP15002K	pH 150 Meter Kit	✓				✓	✓	✓				✓	
ECCONWP15003	CON 150 Meter & Electrode				✓		✓						
ECCONWP15003K	CON 150 Meter Kit				✓		✓	✓					✓
ECPHWP45000	pH 450 Meter Only						✓						
ECPHWP45002	pH 450 Meter & Electrode	✓				✓	✓						
ECPHWP45002K	pH 450 Meter Kit	✓				✓	✓	✓				✓	
ECCONWP45003	CON 450 Meter & Electrode				✓		✓						
ECCONWP45003K	CON 450 Meter Kit				✓		✓	✓					✓
ECDOWP45000	DO 450 Meter Only												
ECDOWP45003	DO 450 Meter & Electrode						✓						
ECDOWP45003K	DO 450 Meter Kit						✓	✓	✓	✓			
ECPDWP45000	PD 450 Meter Only												
ECPDWP45004	PD 450 Meter & Electrodes		✓				✓						
ECPDWP45004K	PD 450 Meter Kit		✓				✓	✓	✓	✓	✓	✓	
ECPCWP45000	PC 450 Meter Only							✓					
ECPCWP45004	PC 450 Meter & pH & Con/ATC Electrodes	✓			✓		✓						
ECPCWP45004K	PC 450 Meter Kit	✓			✓		✓	✓	✓	✓		✓	✓
ECPCWP45003	PC 450 Meter & Combi Electrode			✓									
ECPCWP45003K	PC 450 Meter Combi Kit			✓								✓	✓

# Features

DO 450 and PD 450  
Utilize Optical  
Oxygen Technology



PC 450 Can Accept  
Combi Probe or  
Separate pH/  
Conductivity Probes



81 % Larger Three Line  
Display 450 series  
add backlight

Battery Life Indicator

All Measurements  
Include Temperature  
in °C or °F

View Electrode Slope or  
Probe Efficiency  
At-A-Glance

Calibration Due Reminder  
Set automatic notifications  
from 0 - 60 days

Increased Memory:  
150 points for 150 series,  
500 points with  
date/time for 450 series

450 series offers upgradable  
firmware and also can utilize  
Free Communication Software



Rugged Housing Floats  
& Meets Waterproof  
IP67 Rating  
(With rubber covers)



Utilizes New and  
Improved Grip-Clip™  
Electrode Holder  
(See page 11  
for more details)



Uses Only Two AA  
Batteries or  
Optional Universal  
Power Supply



Integral Built-In-Stand  
for table use or  
wall mounting



450 Models Offer  
Output for  
USB or RS232





# WolfLabs

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

**[www.wolflabs.co.uk](http://www.wolflabs.co.uk)**

**Tel : 01759 301142**

**Fax : 01759 301143**

**[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)**

Please contact us if this literature doesn't answer all your questions.