

Design

- Digital control with digital readout
- Fan assisted air circulation via premixing chamber
- Full P.I.D. heating/cooling control to ensure stable internal temperature
- Pre-set 70°C safety cutout for total cabinet protection
- Electronics RF and TV suppressed
- Hermetically sealed refrigeration system
- Self-evaporating condensate drip-tray
- Automatic defrost
- Doorlock
- RJ 45 interface

Operation

- Controls easy to read and simple to use
- Temperature range -10°C to +50°C (excluding interior illumination and double glazed door models) with an average variation of $\pm 0.5^\circ\text{C}$ and a fluctuation of 0.1°C with an average workload
- Temperature set by direct reading digital controller


Optional Extras

- Automatic dual temperature control
- Interior LED lighting
- Inner clear perspex door
- Built in paper less chart recorder
- Manual high/low temperature audible and visual alarm system with safety cut-out
- Access porthole
- Special evaporator for corrosive conditions
- Internal socket outlet
- Fully programmable controller


The standard voltage is 240v 50Hz but other volts/cycles are available.

Model		600	1200
External dimensions (mm)	Height	2080	2080
	Width	800	1500
	Depth	900	900
Capacity	(litres)	600	1200
Shelf Size	(mm)	530 x 550	530 x 550
Number of Shelves		5	10
Unladen Weight	(kg)	160	235
	A	1500	1500
	B	680	680
	C	1370	1335
	D	135	125
Internal dimensions (mm)	E	420	480
	F	90	450
	G	420	450
	H	180	165
	J	35	115
	K	600	1350

Model 600



Model 1200



LMS Limited reserve the right to amend the specification of all models without prior notice in the light of changing user techniques.



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

