



Affordable Balance to Achieve Reliable Results


The Pioneer PX combines essential weighing functionality with competitive performance, offering high accuracy and repeatability for applications in laboratory, industrial and education settings. The PX is affordably priced, intuitively designed for intelligent operation with a second line display for additional information, and USB and RS-232 connectivity for easy communication.

Unique Features Include:

- The PX offers high accuracy and repeatability for essential weighing applications in laboratory, industrial and education settings at an economical price point.
- Featuring a cast metal lower housing, sub-pan and stainless steel weighing pan, the PX is durably constructed for versatile, long-term use.
- PX features a second line display for additional information/guidance, & USB/RS232 connectivity for easy communication. Draftshield models feature a static removal (ESR) bar for convenient grounding.

PIONEER® Semi-Micro, Analytical and Precision Balances

RS-232 and USB device ports allow for easy connectivity to PCs and PLCs. Equipped with a security lock to prevent unauthorized use.



Large viewing angle with bright backlit LCD display.

2 line display provides additional information or guidance prompts to the user.




Four quick keys enable easy operation of multiple weighing modes.

InCal™ Model	PX323	PX523	PX623	PX3202	PX5202	PX6202	PX4201
ExCal Model	PX323/E	PX523/E	PX623/E	PX3202/E	PX5202/E	PX6202/E	PX4201/E
Approved Model*	PX323M	PX523M	PX623M	PX3202M	PX5202M	PX6202M	PX4201M
Verification Interval (e) (g)	0.01			0.1			1
Class (Approved Models)**	II						
Capacity (g)	320	520	620	3200	5200	6200	4200
Readability (g)	0.001			0.01			0.1
Repeatability (sd.), ≤5% of Full Load (g)	0.0008			0.008			0.08
Repeatability (sd.), 5% of Full Load to Full Range (g)	0.001			0.01			0.1
Linearity deviation, Typical (g)	± 0.0006			± 0.006			± 0.06
Linearity deviation (g)	± 0.002			± 0.02			± 0.2
Stabilization Time (s)	2			1			
Sensitivity Temperature Drift (PPM/K)	± 3						± 10
Min-Weight (typical) (USP, K=2, U=0.10%)	1.6 g			16 g			160 g
Min-Weight (optimal) (USP, K=2, U=0.10%, SRP≤0.41d)***	0.82 g			8.2 g			82 g
Units	Milligram, Gram, Kilogram, Ounce, Pound, Carat, Pennyweight, Ounce Troy, Grain, Newton, Hong Kong Tael, Singapore Tael, Taiwan Tael, Momme, Tical (MM), Mesghal, Tola (India), Baht, 1 Custom unit						
Units (Approved Models)	g, mg, ct			g, kg, ct			
Applications	Basic Weighing, Parts Counting, Percent Weighing, Animal Weighing, Density Determination						
Pan Size (Ø)	120 mm			180 mm			
Power Supply	Power Input: 100 – 240V ~ 200mA 50 – 60Hz 12 – 18VA Power Output: 12 VDC 0,5A						
Assembled Dimensions (W × D × H)	209 × 321 × 309 mm			209 × 321 × 98 mm			
Communication	RS232 and USB						
Operating Temperature Range	Operating conditions for ordinary lab application: +10°C to 30°C (operability guaranteed between +5°C and 40°C).						
Net Weight	4,5 kg			3,5 kg			
Shipping Weight	7 kg			5 kg			
Shipping Dimensions (W × D × H)	507 × 387 × 531 mm			550 × 385 × 291 mm			

*Approved models are all internal calibration models **Approved models only ***The value for SRP is the standard deviation for n replicate weighings (n≥10)

PIONEER® *Semi-Micro, Analytical and Precision Balances*

Outline Dimensions



Other Standard Features and Equipment

Metal base, plastic top housing, removable stainless steel pan, removable glass draftshield or side doors, Real Time Clock with GLP/GMP Data, integrated weigh-below-hook, security bracket, calibration lock and in-use cover, user-selectable environmental filters and brightness settings, auto-tare, auto-dim, user-selectable span calibration points, overload indicator, software lockout and reset menu, user-selectable communication settings and data print options, user-definable project and user IDs, software overload/underload indicator, stability indicator, 11 operating languages

Compliance

- **Metrology (PX...M... models only):** EN 45501; OIML R76
- **Product Safety:** IEC/EN 61010-1; CAN/CSA C22.2 61010-1; UL 61010-1
- **Electromagnetic Compatibility:** IEC/EN 61326-1 Class B, basic environments; FCC Part 15 Class A; Canada ICES-003 Class A
- **Compliance Marks:** CE; CSA

Accessories

Auxiliary Display	30472064
Density Kit for Solids	80253384
Sinker Glass for Density Determination	83034024
Printer SF40A	30064202
SF40A Ink Ribbon Cassette	12120798
SF40A Paper Roll, 57,5 mm (2 Rolls)	12120799
Security Device	80850043
In-use Cover	30372546
Dust Cover (for 0,1 mg and 1 mg models)	30093334
Stand-alone Ionizer ION-100A	30095929
RS232 Cable (9-pin)	00410024
Interface Cable, USB (Type A to B)	83021085



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.