



Valor[®] 2000

Compact Bench Scales



V22PW



V22XW

A durable, rapid-response food processing scale that enhances safety, efficiency, and productivity even in harsh environments!

The OHAUS Valor 2000 water resistant food scale raises the bar and sets a new industry standard with the winning combination of speed and durability. Available in both stainless steel and plastic housing designs, Valor 2000 offers large LED front and rear displays, food safety and puncture resistant keypads, making it the premiere value scale for use in dry or washdown environments.

Standard Features Include:

- **Knife Proof Keypad Prevents Damage from Sharp Objects**—Valor 2000 has a polycarbonate keypad that can endure contact with knives or sharp instruments used daily in demanding food preparation, processing and portioning applications.
- **The Flow-Thru Design Protects Valor 2000 in Harsh Environments**—Safe to use in the weighing of liquids and in wet environments, Valor 2000 is NSF Certified and has an flow-thru design which channels fluids that may enter the housing through strategically located drain holes, ensuring the scale remains clean and operational.
- **Fast Speed and Large Dual Displays Allows More than One Operator to Easily Work on Valor 2000** — With less than half a second stabilization time and front and rear LED displays, multiple operators can efficiently utilize one scale for the same job.
- **Stainless Steel Version Offered with Extra Check Weighing Mode** — The Valor 2000 stainless steel models feature an easy to clean, rigid and protective 304 stainless steel top housing with check weighing mode, expanding its functionality.

Valor[®] 2000 Compact Bench Scale

Knife Proof Keypad Prevents Damage from Sharp Objects

The Valor 2000 is constructed with highly durable 0.5 mm thick polycarbonate keypad which is impact and puncture resistant. Valor 2000's smooth glossy surfaces easily repel stains, moisture, corrosive fluids and food contaminants, and stainless steel models offer an extra layer of protection.

Flow Thru™ Design Protects Valor 2000 in Harsh Environments

The flow-thru, water-resistant design allows for weighing of liquid components and can be used in harsh environments by channeling fluids that may enter the housing to strategically located drain holes, ensuring the scale remains clean and operational. The internal components and connections are silicone sealed to protect the scale from fluids and from condensation that may form inside the scale from constant temperature changes in a typical processing environment. The scale can be easily washed off at the end of each shift to keep it in sanitary condition and avoid the growth of bacteria from food contaminants.

Fast Speed and Large Dual Displays Allow More than One Operator to Easily Work on Valor 2000

Not only does Valor 2000 display results in less than half a second, but with its front and back displays, more than one operator can use the scale for the same job, truly bolstering productivity.

Stainless Steel Version Offered with Extra Check Weighing Mode

The 304 stainless steel Valor 2000's provide an extra layer of protection, as well as an additional checkweighing mode. This ruggedly durable and easy to clean model enhances the scale's usability for all checkweighing applications, including sorting, portioning, and quality assurance.



Rear Display



Power and Portability

The 100-240 VAC universal power adapter can be operated from virtually any power source and can automatically switch to adapt to different power and voltage lines. When plugging in your machine is not an option, the built-in, rechargeable lead acid battery will provide power for 50 continuous hours, ensuring uninterrupted operation for more than a full work week!

Adapter connection cover underneath the scale is spring loaded to ensure the power receptacle is protected from the ingress of moisture, especially when the scale is washed down.

Non-Slip Leveling Feet

Large fully rubberized feet are located at extreme corners of the scale to ensure a wide stance and surface resistance that minimizes the risk of the scale sliding or falling off smooth surfaces. The rubber of the feet extends to the shaft that ensures no grooves are exposed when fully extended; a design that passes NSF standards.

Simple Operation with largest LED display

Valor 2000® was designed with the basic weighing needs of the food industry in mind. The LED display window is 20.5mm high, which is bigger than most competitive products. It is exceptionally easy to setup and operate, resulting in increased productivity.


Application Modes

- **Weighing** — Determine the weight of items in the selected unit of measure.
- **Check Weighing (V22XW only)** — Use the bright red/yellow/green LED's to easily fill containers and packages by weight -- great for sorting, grading and portioning.

Certifications

The Valor 2000 is Certified to NSF/ANSI 169 Special Purpose Food Equipment and Devices and is USDA-AMS Accepted to NSF/ANSI /3-A14159-1 Hygiene Requirements for the Design of Meat and Poultry Processing Equipment.

Dimensions



Valor[®] 2000 Compact Bench Scale

Model	V22PWE1501T V22XWE1501T	V22PWE3T V22XWE3T	V22PWE6T V22XWE6T	V22PWE15T V22XWE15T	V22PWE30T V22XWE30T
Capacity (max) × Readability (d)	1.5 kg × 0.0002 kg 1500 g × 0.2 g)	3 kg × 0.0005 kg 3000 g × 0.5 g	6 kg × 0.001 kg 6000 g × 1 g	15 kg × 0.002 kg 15000 g × 2 g	30 × 0.005 kg 30000 × 5 g
Maximum Resolution	1:7500	1: 6000	1: 6000	1:7500	1: 6000
Weighing Units	V22PW: g / lb * V22XW: g, kg, lb, oz, lb:oz				
Application Modes	V22PW: Weighing V22XW: Weighing, Checkweighing				
Keyboard	V22PW: Two mechanical switches with polycarbonate overlay V22XW: Four mechanical switches with polycarbonate overlay				
Calibration	Digital external span calibration				
Display	7 segment, 6 digital / 20.5 mm high red LED, dual display				
Display Indicators	Stability, center of zero, net, battery status				
Tare Range	To capacity by subtraction				
Zero Range	4% - 20% of Capacity				
Stabilization Time	≤0.5 second				
Overload Capacity	150% of capacity				
Operating Temperature Range	-10 °C to 40 °C, 10% to 90% relative humidity non-condensing				
Construction	V22PW: Stainless steel platform, ABS housing V22XW: Stainless steel platform and housing				
Power	12V DC 0.84A, AC Universal adapter (100-220V AC / 50-60Hz) included				
Battery Life	Internal rechargeable sealed lead-acid battery with 50 hours continuous use				
Ingress Protection	IPX8 Water in water out				
Platform Size	190 × 242 mm				
Scale Dimensions (W × D × H)	V22PW: 280 × 256 × 121 mm V22XW: 288 × 256 × 124 mm				
Shipping Dimensions (W × D × H)	410 × 370 × 220 mm				
Net Weight	V22PW: 3.0 kg V22XW: 3.9 kg				
Shipping Weight	V22PW: 4.0 kg V22XW: 4.9 kg				

Other Standard Features and Equipment

Level bubble, easy-to-transport carrying handle, removable stainless steel platform and chemical-resistant overlay, mechanical keys, spring loaded cover to protect power connector of scale

Compliance

- **Product Safety:** IEC 61010-1; EN 61010-1
- **Electromagnetic Compatibility:** IEC 61326-1; EN 61326-1 - Class B, Basic environments
- **Environmental Protection:** IEC 60529 IPX8
- **Food Safety:** NSF/ANSI 169; NSF/ANSI /3-A 14159-1
- **Other:** RoHS

Accessory

Stainless Steel Platform, 300 x 225 mm 30251753



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.