



*Trinocular metallurgical microscope, 500x,
IOS W-PLAN MET objectives,
incident light only*

Observation Method - Incident Light	Brightfield	Yes
	Oblique	Yes
	Simple polarized light	Yes
Main Body	Type	Upright
	Construction material	Aluminum die-cast
	Trasportation handle	Yes
Head	Type	Trinocular (Siedentopf)
	Split ratio	50/50
	Inclination	30°
	360° rotating	Yes
	Interpupillary distance (mm)	50-75
	Dioptic adjustment	On left tube
	Tube inner diameter (mm)	30
Eyepieces	Field number (mm)	22
	Magnification	10x
	Planar type	Yes
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	26
	High eyepoint (for glass wearers)	Yes
	Rubber cup	Yes
	Retractable protections	Yes
Nosepiece	Positions	Quintuple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
Objectives	Optical system	∞
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	50x-500x
	Type	IOS W-PLAN MET
	Objectives included	5x/0.12, W.D. 15.5 mm
		10x/0.25, W.D. 10 mm
20x/0.40, W.D. 5.8 mm		
50x/0.75, W.D. 0.32 mm		
Stage	Type	Double layer
	Dimensions (mm)	233x147
	Moving mechanism	Rackless
	Moving range (mm)	78x54
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	2
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1

Focusing System	Type	Coaxial coarse & fine
	Coarse total travel (mm)	40
	Fine total travel (per single rotation) (mm)	0.2
	Fine graduations	100
	Fine resolution (µm)	2
	Maximum sample height (mm)	33
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
	Flat knob for ergonomoy	Yes
Accessories Included	Dust cover	Yes
	Tension adjustment tool	Yes
	Allen wrench	Yes
	User Manual	Digital version (downloadable)
Additional Information		
Product Dimensions	Height (mm)	505
	Width (mm)	270
	Depth (mm)	550
Product Weight	(kg)	12.3
Metallographic Attachment	Polarizer	Yes
	Analyzer, 360° rotatable	Yes
	Oblique illumination	Yes
	Field diaphragm	Centerable
	Aperture diaphragm	Centerable
Metallographic Light Source	Light source	X-LED8
	Watt (W)	8
	Lifetime (hours)	> 50,000
	Temperature (K)	6,300
	Brightness control	Yes
Metallographic Power Supply	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug
	Input voltage	100/240 Vac, 50/60 Hz
	Max. power required (W)	13



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.