



*Binocular microscope, 600x,
HC objectives*

| | | |
|---|-----------------------------------|------------------------|
| Observation Method - Transmitted Light | Brightfield | Yes |
| | Simple polarized light | As optional |
| Main Body | Type | Upright |
| | Construction material | Aluminum die-cast |
| Head | Type | Binocular (Siedentopf) |
| | Inclination | 30° |
| | 360° rotating | Yes |
| | Interpupillary distance (mm) | 48-75 |
| | Dioptric adjustment | On left tube |
| | Fixing screw for eyepieces | Yes |
| | Tube inner diameter (mm) | 23 |
| Eyepieces | Field number (mm) | 18 |
| | Magnification | 10x |
| | High eyepoint (for glass wearers) | Yes |
| | Pointer | As optional |
| | Micrometric scale | As optional |
| | Diameter of micrometer glass (mm) | 20 |
| Nosepiece | Positions | Quadruple |
| | Bi-directional | Yes |
| | Rotation on ball bearings | Yes |
| | Objective thread | RMS |
| Objectives | Optical system | 160 |
| | Anti-fungus treatment | Yes |
| | Parfocal distance (mm) | 45 |
| | Standard magnifications | 40x-600x |
| | Type | HC |
| | Objectives included | 4x/0.10, W.D. 18 mm |
| | | 10x/0.25, W.D. 7 mm |
| 40x/0.65, W.D. 0.53 mm | | |
| 60x/0.85, W.D. 0.45 mm | | |
| Stage | Type | Double layer |
| | Dimensions (mm) | 125x116 |
| | Moving mechanism | Rack and pinion |
| | Moving range (mm) | 70x30 |
| | Material | Anti-scratch painting |
| | Specimen holder | Yes |
| | Slide number | 1 |
| | X-Y Vernier scale | Yes |
| | Vernier scale accuracy (mm) | 0.1 |

| | | |
|--|--|--|
| Condenser - Single Position | Type | Abbe |
| | Numerical aperture (N.A.) | 1.25 |
| | Diaphragms | Iris |
| | Centrable | Pre-centered |
| | Focusable | By rotation |
| Focusing System | Type | Coaxial coarse & fine |
| | Coarse total travel (mm) | 16 |
| | Fine total travel (per single rotation) (mm) | 0,4 |
| | Fine graduations | 100 |
| | Fine resolution (μm) | 4 |
| | Upper stop to prevent contact | Yes |
| | Adjustable tension | Yes |
| Transmitted Illumination | Type | X-LED |
| | X-LED type | X-LED1 |
| | Light source power (W) | 1 |
| | Brightness control | Manual |
| | Lifetime (hours) | > 65,000 |
| | Temperature (K) | 6,300 |
| | Max. required power (W) | 1,5 |
| Power Supply for Transmitted Illumination | Type | External |
| | Microscope connector | Jack, 2.1 mm |
| | Power plug type | Multi-plug (EU, UK, US) |
| | Input voltage | 100/240 Vac, 50/60 Hz |
| | Output voltage | 5 Vdc 500 mA |
| Accessories Included | Dust cover | Yes |
| | Tension adjustment tool | Yes |
| | User Manual | Digital version (downloadable) |
| Additional Information | | Mirror for transmitted light (as optional) |
| Product Dimensions | Height (mm) | 350 |
| | Width (mm) | 170 |
| | Depth (mm) | 320 |
| Product Weight | (kg) | 4 |



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

