# B-510PH

v 2.0 2018



## Model: **B-510PH**

#### Typology: ROUTINE MICROSCOPE

## Description:

Laboratory microscope for routine and research applications. Dye-cast frame, with high stability and ergonomy, for transmitted light observation.

Illumination	Light source: X-LED <sup>3</sup> ; light intensity control using a knob on left side of the frame. LED power: 3.6 W, comparable to a 50 W halogen bulb. Color temperature: 6,300 K. LED lifetime: > 65,000 hours. Power supply: Input 110/240 Vac, 50/60 Hz; Output 6 Vdc 2.5 A. Max. required power: 6 W. Köhler illumination system with Field Diaphragm.
Observation Modes	Brightfield, Phase Contrast.
Focusing	Coaxial coarse and fine focusing mechanism (graduated, 0.002 mm) with upper stop, to prevent the contact between objective and specimen. Flat fine focusing knob on the right side. Adjustable tension of coarse focusing knob.
Stage	Double layer with mechanical sliding stage, size 233x147 mm, X-Y movement range 78x54 mm. Belt-drive in X direction. Vernier scale on two axes, accuracy 0.1 mm.
Nosepiece	Quintuple revolving nosepiece, rotation on ball bearings.
Head	Trinocular observation head, inclined 30° and rotatable 360° Diopter adjustment on left eyepiece (+- 5 diopter adjustment). Interpupillary adjustment 50 - 75 mm Fixed photo port, 50/50 ratio.
Eyepieces	Plan Extra Wide Field, PL 10x/22, High Eyepoint.
Objectives	Infinity corrected optical system IOS. - IOS W-PLAN PH 10x/0.25, W.D. 10 mm - IOS W-PLAN PH 20x/0.40, W.D. 5.1 mm - IOS W-PLAN PH 40x/0.65, W.D. 0.54 mm - IOS W-PLAN PH 100x/1.25, W.D. 0.13 mm (oil immersion) All objectives have anti-fungus treatment.
Condenser	Phase condenser (10x/20x, 40x, 100x) with darkfield (dry) and brightfield positions, N.A. 1.25.
Dimensions	HEIGHT: 420 mm WIDTH: 270 mm DEPTH: 390 mm WEIGHT: 9.4 kg
Accessories	Centering Telescope included. Green filter included. Instruction manual and dust cover included.



Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

# www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.