

Monocular brightfield microscope, 400x, multi-plug

| Observation Method - Transmitted Light | Brightfield | Yes |
|---|----------------------------|-----------------------|
| | Simple polarized light | As optional |
| | | |
| Main Body | Туре | Upright |
| | Construction material | Aluminum die-cast |
| | | |
| Head | Туре | Monocular |
| | Inclination | 45° |
| | 360° rotating | Yes |
| | Fixing screw for eyepieces | Yes |
| | Tube inner diameter (mm) | 23 |
| | | |
| Eyepieces | Field number (mm) | 18 |
| | Magnification | 10x |
| | Pointer | As optional |
| | Micrometric scale | As optional |
| | | |
| Nosepiece | Positions | Triple |
| | Bi-directional | Yes |
| | Rotation on ball bearings | Yes |
| | Objective thread | RMS |
| | | |
| Objectives | Optical system | 160 |
| | Anti-fungus treatment | Yes |
| | Parfocal distance (mm) | 45 |
| | Standard magnifications | 40x-400x |
| | Туре | Achromatic |
| | | 4x/0.10, W.D. 10.6 mm |
| | | 10x/0.25, W.D. 7.0 mm |
| | | 40x/0.65, W.D. 0.5 mm |
| | | |
| Stage | Туре | Fixed |
| | Dimensions (mm) | 120x110 |
| | Moving mechanism | As optional |
| | Material | Anti-scratch painting |
| | Specimen clips | Yes |
| | Slide number | 1 |
| | | |
| Condenser - Single Position | Туре | Fixed |
| | Numerical aperture (N.A.) | 0.65 |
| | Diaphragms | Iris |

| Focusing System | Туре | Separated coarse & fine |
|-----------------|--|-------------------------|
| | Coarse total travel (mm) | 13 |
| | Fine total travel (per single rotation) (mm) | 0.1 |
| | Upper stop to prevent contact | Yes |
| | Adjustable tension | Yes |

OPTIKA MICROSCOPES ITALY

| Transmitted Illumination | Туре | LED |
|---|------------------------------------|-------------------------------------|
| | Light source power (W) | 0.5 |
| | Brightness control | Manual |
| | Lifetime (hours) | > 65,000 |
| | Temperature (K) | 6,300 |
| | Max. required power (W) | 1 |
| | | |
| Power Supply for Transmitted Illumination | Туре | External |
| | Microscope connector | Jack, 2.1 mm |
| | Power plug type | Multi-plug (EU, UK, US) |
| | Input voltage | 100/240 Vac, 50/60 Hz |
| | Output voltage | 5 Vdc 500 mA |
| | Rechargeable batteries | Yes |
| | Battery type | Ni-MH (3x, AA size) |
| | Working time of batteries (hours) | up to 8 |
| | Charging time of batteries (hours) | 8 |
| | | |
| Accessories Included | Dust cover | Yes |
| | Tension adjustment tool | Yes |
| | User Manual | Digital version (downloadable) |
| | | |
| Additional Information | | Plane concave mirror (as optional). |
| | | |
| Product Dimensions | Height (mm) | 365 |
| | Width (mm) | 135 |
| | Depth (mm) | 220 |
| | | 220 |
| Product Weight | (kg) | 2.3 |
| | (\\\y) | 2.0 |

OPTIKA MICROSCOPES ITALY



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





