

Jaw Crusher BB 200

General Information

The Jaw Crusher BB 200 is used for the rapid, gentle crushing and pre-crushing of medium-hard, hard, brittle and tough materials. Its variety of materials offered, including heavy-metal free steel, its efficiency and safety makes it ideal for sample preparation in laboratories and industrial plants.

For small amounts of sample the BB 200 can be used batch-wise; for larger amounts it can be operated continuously. Control of the gap width and zero point adjustment allow for reproducible results. The Belleville spring washer protects the unit from overloads and in conjunction with the central lubrication guarantees a long service life.

Stract

Application Examples

alloys, basalt, cement clinker, ceramics, chamotte, coal, coke, construction materials, feldspar, glass, granite, minerals, ores, oxide ceramics, quartz, rocks, silicon, slag, ...

Product Advantages

- excellent crushing performance
- connector for dust extraction
- central lubrication
- suitable for integration in automatic installations
- special version for grinding semi-conductor materials
- wear compensation with zero-point adjustment
- gap width setting
- overload protection
- wide range of materials for contamination free grinding
- no-rebound feed hopper with quick-release clamp
- brake motor with safety switch
- easy-to-clean crushing chamber
- continuous grinding



Jaw Crusher BB 200

Features

Applications coarse and pre-crushing

Field of application chemistry / plastics, construction materials, engineering / electronics,

environment, geology / metallurgy, glass / ceramics

Feed material medium-hard, hard, brittle, tough

Size reduction principle pressure

Material feed size* < 90 mm

Final fineness* < 2 mm

Material of grinding tools manganese steel, stainless steel, tungsten carbide, steel 1.1750 (for heavy-

metal free grinding)

Jaw width90 x 90 mmGap width setting0 - 30 mmGap width displayscale

Zero point adjustment yes
Hinged hopper yes
Dust extraction unit yes
Central lubrication optional
Process line version optional

Collector capacity 5 I

Drive 1-phase motor / 3-phase motor

Drive power 1.5 kW Protection code IP 54

W x H x D closed 450 x 1160 x 900 mm

Net weight ~ 300 kg

Workplace related emission

value

LpAeq 92 dB(A)

Documentation Operation & Application Video

Standards CE

Function Principle

The Jaw Crusher BB 200 is a robust and powerful forced-feed crusher. The feed material passes through the no-rebound hopper and enters the crushing chamber. Size reduction takes place in the wedgeshaped area between the fixed crushing arm and one moved by an eccentric drive shaft. The elliptical motion crushes the sample which then falls under gravity.

As soon as the sample is smaller than the discharge gap width, it falls into a removable collector. The continuous gap width setting with scale ensure optimal size reduction in accordance with the set gap width value



^{*}depending on feed material and instrument configuration/settings



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.