

#### **General Information**

The BB 50 has been specially designed for sample preparation in the laboratory. It is used for the rapid, gentle crushing and pre-crushing of medium-hard, hard, brittle and tough materials.

The space-saving, dust-tight instrument fits on any laboratory bench and is ideally suited to crush small amounts of sample with large feed sizes gently and without loss. To avoid metallic contamination, the grinding chamber is available of ceramic materials. With its digital gap width display and zero point adjustment the BB 50 allows for reproducible results.

## **Application Examples**

alloys, basalt, bones, cement clinker, ceramics, chamotte, coal, coke, construction materials, feldspar, glass, granite, minerals, ores, oxide ceramics, quartz, rocks, silicon, slag, ...

## **Product Advantages**

- powerful size reduction thanks to 1.1 kW industrial drive
- large fold-back hopper
- · dust-tight housing
- · compact, benchtop instrument
- · removable jaw for easy cleaning
- · adjustable speed allows adaptation to sample characteristics
- · wear compensation with zero-point adjustment
- convenient operating keypad with digital display
- · memory for gap width setting
- adjustable speed and convenient operating keypad
- wide range of materials for contamination free grinding

#### **Features**

Applications coarse and pre-crushing

Field of application agriculture, biology, construction

materials, geology / metallurgy, glass / ceramics, medicine /

pharmaceuticals, ...

Feed material medium-hard, hard, brittle, tough

Size reduction principle pressure

Material feed size\* < 40 mm

Final fineness\* < 0.5 mm

Material of grinding tools manganese steel, stainless steel,

tungsten carbide, zirconium oxide, steel 1.1750 (for heavy-metal free

grinding)

Jaw width 45 x 59 mm





Gap width setting 0 - 11 mm in increments 0.1 mm

Gap width display digital
Zero point adjustment yes
Hinged hopper yes

Dust extraction unit already dust-tight

Central lubrication lifetime lubrication by manufacturer Process line version process line use is possible by

removing drawer

Collector capacity 3 I

Drive 3-phase motor with frequency

converter

Drive power 1.1 kW

Electrical supply data different voltages

Power connection 1-phase

Protection code IP 20 / IP 00 at ventilation slots

W x H x D closed 420 x 460 x 560 mm

Net weight ~ 79 kg

Documentation Operation & Application Video

Standards CE

<sup>\*</sup>depending on feed material and instrument configuration/settings



#### **Videolink**



http://www.retsch.com/bb50

## **Function Principle**

The Jaw Crusher BB 50 is a robust and powerful forced-feed crusher. The feed material passes through the no-rebound hopper and enters the crushing chamber. Size reduction takes place in the wedgeshaped area between the fixed crushing arm and one moved by an eccentric drive shaft. The elliptical motion crushes the sample which then falls under gravity.

As soon as the sample is smaller than the discharge gap width, it falls into a removable collector. The continuous gap width setting with digital display ensure optimal size reduction in accordance with the set gap width value.

#### Order data

#### Jaw Crusher BB 50

#### breaking jaws / wearing plates

20.062.0001	BB 50, 200-240 V, 50/60 Hz, manganese steel / stainless steel
20.062.0002	BB 50, 200-240 V, 50/60 Hz, stainless steel / stainless steel
20.062.0003	BB 50, 200-240 V, 50/60 Hz, tungsten carbide / tungsten carbide
20.062.0004	BB 50, 200-240 V, 50/60 Hz, zirconium oxide / zirconium oxide

#### for grinding without heavy-metal contamination

20.062.0005 BB 50, 200-240 V, 50/60 Hz, steel 1.1750 / steel 1.0344

## other electrical versions available for the same price

#### **Accessories BB 50**

22.048.0014 Breaking jaws, manganese steel, 1 pair 22.048.0012 Breaking jaws, stainless steel, 1 pair



22.048.0010	Breaking jaws, tungsten carbide, 1 pair
22.048.0011	Breaking jaws, zirconium oxide, 1 pair
22.711.0015	Wearing plates, stainless steel, 1 pair
22.711.0016	Wearing plates, tungsten carbide, 1 pair
22.711.0017	Wearing plates, zirconium oxide, 1 pair
03.050.0437	Cover plate for collecting receptacle
05.242.0038	V-belt, 1 piece
22.825.0005	Carry handles, 1 pair

## Accessories BB 50 for grinding without heavy-metal contamination

22.048.0016	Breaking jaws, steel 1.1750, 1 pair
22.711.0018	Wearing plates, steel 1.0344, 1 pair



# **Wolf Laboratories Limited**

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





