



Excellence in Quality and Convenience

Sartorius pipette tips meet the highest quality and purity standards.

Sartorius tips are designed and manufactured to fit Sartorius pipettes perfectly, enabling maximum tip sealing and accuracy. This combination guarantees the highest performance and precision for your pipetting needs. Moreover, correctly fitting tips protect the pipette's tip cone from wear and tear.

Sartorius tip packages are designed to make the daily work of lab rofessionals easier. Our offering covers a variety of functional tip package options with various purity ratings.

The high purity and consistent quality of Sartorius tips provide your valuable samples with the ultimate protection from contamination. We adhere to strict quality standards and control procedures – from raw material to automated manufacturing and packaging.

Pure Quality

- Tips are manufactured using a fully automated process in ISO class 8 cleanroom conditions to ensure purity
- Strict standards, followed from R&D to production and delivery: ISO 9001, ISO 140001, and ISO 13485
- Every batch of purity certified tips is tested and verified as free of DNase, RNase, and endotoxins
- Using Sartorius tips with Sartorius pipettes guarantees perfect tip sealing, ensuring reliable results with high precision and accuracy
- Tip-purity certificates can be easily downloaded from our website, www.sartorius.com
- Tips are manufactured using virgin polypropylene without any additives





Convenient

- Smart color codes make it quick and easy to find the right tip for your pipette
- Versatile package options are available for various needs
- Sartorius pipettes feature Optiload[®] and Optiject[®] functions for smooth tip attachment and ejection
- Pre-sterilized tips are available for demanding applications
- Compatible with most pipette brands

Fully Compliant

- Every tip package is clearly marked with the volume, colour code, purity grade, expiry date, product code, and lot number
- The lot number enables full traceability right from production
- CE | IVD compliant when used with Sartorius pipettes

High Quality Tips for Various Pipetting Applications

Optifit Tips – Standard Multipurpose Tips for Various Applications

Optifit Tips are high-quality standard tips and an excellent solution for various applications. Non-filter Optifit Tips are available in various purity levels and package options, and are suitable for use with other manufacturers' pipettes. Optifit Tips are also fully autoclavable at 121°C for 20 minutes with 1 bar/100 kPa pressure.

Optifit Tip Range

- Extended and wide-bore tips for specific applications
- Pre-sterilized and non-sterile
- Purity certified Single Tray racks and Refill Packs
- Single Tray racks, Refill Packs, Refill Towers and Bulk packages
- Volume range from 10 µl to 10 ml

SafetySpace Filter Tips – Filter Tips for Contamination Protection

SafetySpace Filter Tips help prevent cross-contamination of your sample and pipette, and reduce the need for pipette maintenance. Sartorius SafetySpace Filter Tips have more space between the sample and the filter than conventional filter tips, which prevents the risk of the sample coming into contact with the filter. The filter is made of polyethylene and does not include any self-sealing additives.

SafetySpace Filter Tips provide protection from contamination for pipettes and samples in the following applications:

- Molecular biology
- Microbiology
- Cell cultivation
- Radioactive lab work

SafetySpace Filter Tip Range

- Pre-sterilized
- Purity certified
- Single Tray racks
- Volume range from 10 to 1,200 µl





Low Retention Tips – Hydrophobic Tips for Maximum Sample Recovery

Low Retention Tips maximize sample recovery and the accuracy of results when pipetting detergent containing solutions or other liquids with low surface tension. Using patented Sartorius technology, we can manufacture tips with fully hydrophobic and highly liquid-repellent surfaces.Low Retention Tips offer excellent chemical resistance without any leachables.

Low Retention Tips are advantageous, for example, in sensitive molecular biology applications, where reagents often contain viscous substances and detergents. These applications include, for example:

- PCR and real-time PCR
- Cloning, sequencing, and other DNA and RNA techniques
- SDS-PAGE and other protein analysis methods
- Protein purification techniques

Low Retention Tip Range

- Filter (SafetySpace) and non-filter (Optifit) tips
- Pre-sterilized and non-sterile
- Single Tray racks and Refill Towers
- Range of volumes from 10 to 1,200 µl



The four Low Retention Tips on the right retain only minimum residual liquid.

Unique SafetySpace Feature

SafetySpace Filter Tips have additional space between the sample and filter. Any liquid types and pipetting techniques can be applied without the risk of the liquid permeating the filter. The extra space is particularly beneficial in the following applications:

- Pipetting foaming liquids such as buffers and proteins
- When using electronic pipettes with multiple dispensing functions
- Reverse pipetting



SafetySpace – the additional space between the sample and filter.

A Convenient Range of Package Options

Sartorius tip packages are designed to make the daily work of lab professionals easier. Our offering covers a variety of functional tip packages with various purity ratings.

Smart color codes make it quick and easy to find exactly the right tip for your pipette. The trays, racks, and non-filter tips are fully autoclavable for 20 minutes at 121°C and 1 bar/100 kPa. All tips, trays, and racks are made of 100% pure polypropylene and are recyclable as energy waste.

Single Tray Racks

- 96 tips in convenient and reusable tray racks
- Each batch is certified as free of DNase, RNase, and endotoxins
- Informative rack labelling enables easy tip identification and traceability
- Hermetically sealed plastic wrapping ensures purity
- Empty racks can be easily reloaded with tips from Refill Towers and Packs



Refill Packs

The fast and easy way to refill empty Single Tray racks.

Refill Tower

- Reuse and reload empty racks easily
- Save space: 10x96 tips in each tower
- Available in the most widely used tip sizes: 10 μ l, 200 μ l, and 350 μ l
- 100% recyclable cardboard package



Refill Packs

- Reuse and reload empty racks easily
- Each batch is certified as free of DNase, RNase, and endotoxins
- Individually packed hermetically sealed tip trays for maximum purity
- Pre-sterilized option available



Bulk Packs

Bulk packages of high-quality tips

FlexiBulk®

- Fast and convenient reloading of racks due to orderly packed tips.
- Compact and airtight resealable plastic package



Bulk in a Box

- Economical resealable bag of tips in cardboard packaging
- Available in 10 μ l, 5 ml, and 10 ml





Ordering Information

We have the second

Optifit Tips and Optifit Low Retention Tips

ackage			Single Tray (10×96	·					
ow Retention				Low Retention					
Purity			Free of DNase, RNase, endotoxins	Free of DNase, RNase, endotoxins					
0,1 – 10 μl,	31.5 mm	Non-sterile	790010	LH-L790010					
		Pre-sterilized	790011						
0,1 – 10 μΙ	46 mm	Non-sterile	783210						
Extended		Pre-sterilized	783211						
0,5 – 200 μΙ	51 mm	Non-sterile	790200	LH-L790200					
		Pre-sterilized	790201						
5 – 350 μl	54 mm	Non-sterile	790350	LH-L790350					
		Pre-sterilized	790351						
10 – 1,000 μΙ	71.5 mm	Non-sterile	791000	LH-L791000					
		Pre-sterilized	791001						
10 – 1,000 μΙ	68.5 mm	Non-sterile	791020						
Wide bore		Pre-sterilized	791021						
50 – 1,200 μl	71.5 mm	Non-sterile	791200	LH-L791200					
		Pre-sterilized	791201						
50 – 1,200 μl	90 mm	Non-sterile	791210	LH-L791210					
Extended -		Pre-sterilized	791211						
100 – 5,000 μΙ	150 mm	Non-sterile	780304 (50 tips)						
1 15		Pre-sterilized	780305 (50 tips)						
T									
1 – 10 ml	155 mm	Non-sterile							
				-					









Refill Pack Refill Tower (10×96 tips)

FlexiBulk[®]

Bulk in a Box

Refill Pack	Keriii Tower (10)	(96 tips)	FIEXIBUIK	Bulk in a Box			
		Low Retention					
Free of DNase, RNase, endotoxins							
	790012	LH-L790012		790014 (1,000 tips)			
790013 (20×96 tips)							
	790202	LH-L790202	LH-B790204 (960 tips)				
790203 (15×96 tips)							
	790352	LH-L790352	LH-B790354 (960 tips)				
790353 (15×96 tips)							
791002 (10×96 tips)			LH-B791004 (480 tips)				
791003 (10×96 tips)							
			LH-B791204 (480 tips)				
791202 (10×96 tips)			LH-B791204 (480 tips)				
791203 (10×96 tips)							
791212 (10×96 tips)							
791213 (10×96 tips)							
				700000 (100 1)			
				780300 (100 tips) 780308 (1,000 tips)			
	Free of DNase, RNase, endotoxins 790013 (20×96 tips) 790203 (15×96 tips) 790353 (15×96 tips) 791002 (10×96 tips) 791202 (10×96 tips) 791203 (10×96 tips) 791212 (10×96 tips)	Free of DNase, RNase, endotoxins 790012 790013 (20×96 tips) 790202 790203 (15×96 tips) 790352 790353 (15×96 tips) 791002 (10×96 tips) 791003 (10×96 tips) 791202 (10×96 tips) 791203 (10×96 tips) 791212 (10×96 tips)	Low Retention	Low Retention Free of DNase, RNase, endotoxins 790012			

LH-780316 (250 tips)

Ordering Information

SafetySpace Filter Tips and SafetySpace Low Retention Tips



Single Tray (10×96 tips)

ackage			Single Tray (10×96 t	ips)
ow Retention				Low Retention
urity			Free of DNase, RNase, endotoxins	Free of DNase, RNase, endotoxins
0.1 – 10 μΙ	3.5 mm	Pre-sterilized	790011F	LH-LF790011
0.5 – 20 μΙ	51 mm	Pre-sterilized	790021F	LH-LF790021
2 – 120 μΙ	51 mm	Pre-sterilized	790101F	LH-LF790101
5-200 μΙ	52.5 mm	Pre-sterilized	790201F	LH-LF790201
5 – 300 μl	52.5 mm	Pre-sterilized	790301F	LH-LF790301
50 – 1,000 μl	78 mm	Pre-sterilized	791001F	LH-LF791001
50 – 1,200 μl	90 mm	Pre-sterilized	791211F	LH-LF791211
0,1 – 10 μl Extended, with standard air gap	46 mm	Pre-sterilized	783201	











Protect Your Pipette and Sample with Safe-Cone Filters

Safe-Cone Filters act as a final barrier to prevent any fluids and liquid vapors from coming into contact with the internal components of the pipette. These unique and replaceable filters are made of polyethylene (PE). They:

- protect the pipette and sample from contamination
- prolong the pipette's lifetime
- reduce maintenance intervals

Safe-Cone Filters cannot be used together with filter tips.

Plus Filter

For more demanding applications such as radioactive work, cell culture, bacterial and virological work, and molecular biology.

Standard Filter

For general applications. These filters can be used for the same applications as the Plus filter, but need to be changed more frequently.



Removing the Safe-Cone Filter

Safe-Cone Filters

Order Code	Item	Qty/Unit			
721008	Standard ∅ 2.51 mm PE	50			
721007	Standard ∅ 3.15 mm PE	50	_		
721006	Standard ∅ 5.33 mm PE	50			
721005	Standard Ø 6.73 mm PE	50			
721014	Standard ∅ 1.83 mm PE	50			
721018	Plus Ø 2.51 mm PE	50			-
721017	Plus Ø 3.15 mm PE	50			-
721016	Plus Ø 5.33 mm PE	50	112		
721015	Plus Ø 6.73 mm PE	50		lij.	
PE = polyethylene				To the state of th	
					SHr. Street Street

Sartorius Design and R&D – The Driving Force Behind Our High-Quality Products

Customer needs are always the starting point when developing and manufacturing Sartorius pipettes and pipette tips. As our customers have their own unique preferences and because pipetting needs vary between applications and users, we provide our customers with liquid handling equipment that matches their applications precisely and fulfills even the strictest quality standards. Ergonomics, performance, and reliability are the cornerstones of our design and product development processes. Strong technical innovation and the latest design and manufacturing technologies ensure the high quality and performance of our products.

Sartorius has a rich and extensive history in liquid handling. Our experience and knowledge of pipette and pipette tip design has resulted in several award-winning innovations and products. The Sartorius liquid handling competence center masters the entire value chain, from customer needs and product design to manufacturing. Our in-house R&D capabilities with experienced liquid handling experts enable continuous product and process development and the creation of new, innovative solutions. Designing Sartorius tips goes beyond mere tip geometry: our R&D team also designs the tip molds in order to ensure the highest possible quality and consistency.


Sartorius has modern production facilities for pipettes and tips. Our highly automated tip manufacturing facility allows us to maintain the highest quality and purity standards by selecting the best plastic materials and controlling the manufacturing process from beginning to end. Our quality management system follows not only ISO 9001 and ISO 14001, but also ISO 13485. Tip production also complies with the ISO 14644–1 standard, in order to fulfill ISO Class 8 cleanroom conditions for guaranteed tip purity.



Ensure the Highest Pipetting Performance and Precision

Sartorius tips are designed and manufactured to perfectly fit with Sartorius pipettes enabling maximum tip sealing and accuracy.

Pipette Tip Selection Guide



Note: Low Retention Tips are available in volumes up to 1,200 $\mu l. \,$

^{*}Filter tip with standard air gap. In tests, 10 µl extended tip's systematic error and random error results, deviated slightly from those of the 10 µl tip.

Ensure the Highest Pipetting Performance and Precision

Sartorius tips are designed and manufactured to perfectly fit with Sartorius pipettes enabling maximum tip sealing and accuracy.

Pipette Tip Selection Guide

		Tacta® and mLINE®						Proline® Plus																	
Mechanical	Pipettes		1-c	h							8 Et	12-	ch	1-c	h								8 Et	12-	ch
	Colour Code	μΙ	0,1-3	0,5-10	2-20	10-100	20-200	100-1,000	200-5,000	1-10 ml	0,5-10	5-100	30-300	0,1-3	0,5-10	2-20	2-50	10-100	20-200	100-1,000	200-5,000	1-10 ml	0,5-10	10-100	30-300
Optifit Tips		0,1-10																							
		0,1-10 Ext.																							
		0,5-200																							
		5-350											•												
		10-1,000																							
		10-1,000 WB																							
		50-1,200																							
		50-1200 Ext.																							
		100-5,000							•												•				
	•	1-10 ml								•												•			
SafetySpace		0,1-10																							
Filter Tips		0,1-10 Ext.*																							
		0,5-20																							
		2-120																							
		5-200																							
		5-300																							
		50-1,000																		•					
		50-1,200																							

Note: Low Retention Tips are available in volumes up to 1,200 μl.

^{*}Filter tip with standard air gap. In tests, 10 µl extended tip's systematic error and random error results, deviated slightly from those of the 10 µl tip.

Proline [®]															
Mechanical I	Pipettes		1-c	h							8 & 12-ch				
	Colour Code	μΙ	0,1-2,5	0,5-10	2-20	5-50	10-100	20-200	100-1,000	1,000-5,000	0,5-10	2-50	50-300		
Optifit Tips	•	0,1-10													
		0,1-10 Ext.													
		0,5-200													
	•	5-350													
		10-1,000													
		10-1,000 WB							•						
		50-1,200													
		50-1,200 Ext.													
		100-5,000								•					
	•	1-10 ml													
SafetySpace		0,1-10													
Filter Tips		0,1-10 Ext.*													
		0,5-20													
	•	2-120					•								
	•	5-200													
		5-300													
		50-1,000													
		50-1,200													



Ergonomic and Reliable Sartorius Pipettes

Sartorius pipettes provide the perfect solution for your liquid handling needs. Sartorius pipettes and tips fit seamlessly together and provide you with maximum pipetting performance and exact accuracy and precision. Sartorius offers the leading range of superior electronic and mechanical pipettes. For more information, visit www.sartorius.com. Sartorius also provides pipette maintenance, repair, and calibration services globally. Contact your nearest Sartorius service center or office for more information.



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.