

	Weight (g/m ²)	Thick. (mm)	Strength - Burst (kpa)		Pore size - Retention (Coulter Porometer II) average diam. In um			Filter Speed (s) per ml	
			Drv	Wet	max.	medium	min.		
FILPAP									
	53	0.18	72	41	28.2	16.2	7.3	7	
FP	62	0.21	146	80	28.4	15.3	8.8	9	
	65	0.15	72	26	15.9	9.2	3.1	21	
FS	64	0.14	-	-	14.5	8.6	3.9	22	
F1/KA4	86	0.17	133	26	8.5	5.4	3.2	70	medium
	90	0.19	85	23	11.8	5.4	3.2	57	
F4/KA2	83	0.19	88	25	15.3	9.5	5.1	19	fast
	88	0.2	81	25	19.8	10.6	5.1	15	
F2/KA5	82	0.17	130	24	5.6	4.1	2.4	102	medium
	97	0.18	125	25	8.4	5.3	3.3	62	



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.