

QS25 25Litre Ultrasonic Bath

Ultrawave's **Q-Series** offers outstanding performance for use in medical, scientific, laboratory, chiropody, veterinary and many other professional environments. **Q-Series** Ultrasonic Cleaners are Class I Medical Devices, compliant to MDR (EU) 2017/745.

Incorporating Ultrawave's Frequency Leap Technology, homogenous cavitational activity is generated throughout the ultrasonic bath reducing dead spots and standing waves. This provides a more consistent scrubbing action for excellent results.





The **QS25** is a 25Litre heated, digital ultrasonic bath.

The menu driven control panel allows simple adjustment of cycle time (0 to 99 minutes), temperature (ambient to 70°C), ultrasonic power and frequency mode for precise and accurate processing.

Combining features such as degas mode, fluid level sensor and a memory card port, the **QS25** offers repeatable and traceable cleaning performance with consistent cleaning results every time.

Specifications are subject to change for continual improvements

Company Reg VAT No EROI No UW-DC-112-31 2558071 GB 827 1111 60 GB827111160001 Version 3





QS25

25Litre Ultrasonic Bath

Construction Case	304 Stainless Steel
Construction Tank	304 Stainless Steel
Control	Digital LCD
Overall Dimensions	550 x 490 x 365mm (WxDxH)
Tank Dimensions	505 x 300 x 200mm (WxDxH)
Internal Basket Dimensions	465 x 265 x 160mm (WxDxH)
Maximum Capacity	28Litres
Working Capacity	25Litres
Ultrasonic Power	400W
Ultrasonic Power (per litre)	16W/Litre
Operating Frequency	32 – 38kHz <i>Frequency Leap</i>
Maximum Heating Capacity	Ambient - 70°C
Maximum Heating Capacity Heater Power	Ambient - 70°C 650W
Heater Power	650W
Heater Power Timer	650W 0 - 99 minutes
Heater Power Timer Mains Connection	650W 0 - 99 minutes 230VAC
Heater Power Timer Mains Connection Drain Outlet	650W 0 - 99 minutes 230VAC ¹ /2" BSP valve (located at rear of machine)
Heater Power Timer Mains Connection Drain Outlet Lid Basket Gross Weight	650W 0 - 99 minutes 230VAC ¹ /2" BSP valve (located at rear of machine) ABS Plastic
Heater Power Timer Mains Connection Drain Outlet Lid Basket Gross Weight (inc. lid, basket & packaging)	650W 0 - 99 minutes 230VAC ¹ /2" BSP valve (located at rear of machine) ABS Plastic 304 Stainless Steel 18.5kg
Heater Power Timer Mains Connection Drain Outlet Lid Basket Gross Weight	650W O - 99 minutes 230VAC ¹ /2" BSP valve (located at rear of machine) ABS Plastic 304 Stainless Steel

(within 30days of purchase)

Company Reg VAT No EROI No UW-DC-112-31 2558071 GB 827 1111 60 GB827111160001 Version 3





Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.